

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 74)

Set a Maple post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S12 on N. and S13 on S. faces; from which
 An Alder 24" dia., bears N.85°E., 47 lks. dist. mkd. ¼ S12 BT.
 An Elder 4" dia., bears S.28°W., 14 lks. dist. mkd. ¼ S13 BT.

Survey by G.R. Lecklider - For: Mrs. M.A. Patrick - Feb. 1958 - M 8-38

Set 1.9 chs. West of creek.
Set 1½" Pipe and 8 x 8 post.
 14" Fir N.35°E., 92.5 ft.
 22" Spruce S.10°W., 45.5 ft.

Survey by Clyde Mulkins LS #2008 - For: Sparrow-Pacific and Richard Holmes - Oct. 30, 1987 - M 101-31

Found - 1½" Iron pipe.
 20" Fir N.34½°E., 92.5 ft. with healed face.
 Hemlock stump N.18½°E., 53.0 ft. to face. (Rec. S.10°W., 45.5 ft.)
New BTs -22" Spruce N.28°E., 6.6 ft.
 11" Hemlock S.44°E., 43.1 ft.
Replaced I.P. with 3/4" x 30" rebar with 2" alum. cap.

FD. OK - Robert Ward - June 1996 - M 125-12

Fd. OK Sept. 1999 by T. Hostetter added 6 ft. fence post 1 ft. south - see M133-40.