

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 1

Alias	Description

Survey by Perry Fox - For: Davidson Industries - June 1981 -
C.S. File 58/238(n) and M 88-13

Set 2½" brass cap, from which
24" Maple bears S.64°W., 30.8 ft.
12" Alder bears S.29°E., 20.2 ft.
9" Spruce bears N.40°E., 29.8 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen
Flause, crew - July 26, 1988 - C.S. File 62/64 & M 101-51
(Map filed April 1989)

Found - 1981 2½" dia., brass cap on a 2¼" O.D. iron pipe,
protruding 10" above ground. Cap is stamped "PLS
1457 T20S R12W C ¼ S1 1981".

A 1/2" Iron pipe 46" long, loosely set and
protruding approx. 40" above ground.

(Bearings and distances to M 88-13 BC/IP:

24" now 26" dia., Maple with a possible fully healed
blaze, bears S.64°W., 30.8 ft. (agrees w/rec)

12" now a 13" dia. Alder with bark scribing "C ¼ BT
S1", bears S.29°E., 19.3 ft. (Rec. S.29°E., 20.2
ft.)

9" now 11" dia. double trunked Spruce, a fully
healed blaze is on pistol butt South trunk.
Center of root crown bears N.45°E., 27.7 ft.
(Rec. N.40°E., 29.8 ft.)

Set a 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 42" long
Iron pipe protruding 6" above ground, from which

26" dia. Maple with a possible fully healed blaze
bears S.68°W., 29.8 ft.

13" dia. Alder with bark scribing "C ¼ BT S1" bears
S.35°E., 15.7 ft.

11" dia. double trunked Spruce, a fully healed blaze
is on pistol butt South trunk. Center of root
crown bears N.37°E., 30.5 ft.

A 1981 2½" BC/IP bears N.3°E., 3.3 ft.

Fd. OK, June 1990 - M 110-42

FD. BC by Brent Knapp, 1/2013 - M164-59