

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 678600

PRIMARY CORNER DESCRIPTION M.C. So. bdy. Sec. 1

Alias <u>965050</u>	Description <u>M.C. N. side Lake Tsiltcoos</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 22)

-----  
Leave Lake. Set post, from which  
A Fir 36" dia., bears S.19°W., 21 lks. dist.  
A Fir 36" dia., bears N.13°E., 47 lks. dist.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 70)

-----  
Re-establish the meander cor. bet. secs. 1 and 12 on W. margin of lake by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, and marked MC on the W.; T20S R12W on the E.; S1 on the N.; and S12 on the S. faces, from which  
A Spruce 5" dia., bears S.21°W., 21 lks. dist. mkd. T20S R12W S12 MC BT.  
An Alder 10" dia., bears N.13°W., 14 lks. dist. mkd. T20S R12W S1 MC BT.

The remains of the old witness trees are recognizable and are fully connected with this cor., as described in the notes furnished by the surveyor general.

Survey by G.R. Lecklider - For: Mrs. M.A. Patrick - Feb. 1958 - M 8-38

-----  
Found scribed post.  
Set 12" Fir, N.40°W., 16.5 ft.

Fd. OK, August 1980 by P. Fox - M 84-71

Survey by Robert A. Manseth - For: R.E. Chapman - April 24, 1975 - C.S. File 58/116

-----  
Found 5/8" rebar.  
Set - Spike in scribed 16" D.Fir, N.34°27'W., 14.18 ft. to head of spike.  
Spike in center line road, S.3°45'20"W., 23.76 ft. to spike.

Fd. OK Aug. 1980 by P. Fox - M 84-71  
Fd. OK March 1991 - C.S. File 63/70  
Fd. OK, July 1992 by Wobbe - M 115-42  
Fd. OK, Nov. 1993 by Manseth - M 124-21  
Found OK by Manseth, 4/1998 - M 129-1 A&B