

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25 & 36, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 9)

-----  
Set post corner of secs. 25, 30, 31, & 36; from which  
An alder, 24" dia, bears S.40°E., 8 lks.  
A Spruce, 30" dia., bears N.18°E., 54 lks.  
A Spruce, 48" dia., bears N.7°W., 25 lks.  
A Spruce, 6" dia., bears S.86°W., 90 lks.

Fd. & used in GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 149-150)

Troy J. Rambo - For: Port Blakely Tree Farms - Oct. 1998 - M 131-9

-----  
Found - A 50" Spruce stump with scribes opened up face, Orig., bears N.18°E., 54 lks. to the face.  
Remains of scribe marks in a very rotten Spruce stump approx. 65", Orig., bears N.7°W., 25 lks., to the face.

Set - 5/8" x 30" rebar with a 2" alum. cap, from which:  
20" Alder bears S.73°E., 6.3 ft., scribed "T20S R12W X BT"  
12" Alder bears S.11°W., 11.3 ft, scribed "T20S R12W S36 BT"  
19" Alder bears N.87°W., 4.9 ft., scribed "T20S R12W S25 BT"

Note - All BT faces painted red, distances measured to a 6" spike at side center base. Bearings were measured with a hand compass (mag. delc. 20°E.) and a 6 ft. steel fence post was set within 2 ft.

Fd. OK by B. Bacon, April 2001 - M138-7  
Found OK by B. Bacon, Oct. 2002 - M141-23