

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 9)

Set ¼ sec. post, from which:
A Fir 12" dia., bears N.23°E., 38 lks. dist.
A V. Maple 4" dia., bears S.75°W., 12 lks. dist.

Troy J. Rambo - For: Port Blakely Tree Farms - Oct. 1998 - M 131-9

Set - 5/8" x 30" rebar with a 2" alum. cap, from which:
20" D.Fir bears N.47°W., 26.9 ft., scribed "¼ S25 BT"
14" D.Fir bears S.65°W., 13.0 ft., scribed "¼ S25 BT"
16" D.Fir bears S.30°W., 24.0 ft., scribed "¼ S25 BT"
20" D.Fir bears S.69°E., 36.8 ft., scribed "¼ X BT"
This position falls on an East-West ridge top.
Note -All BT faces painted red, distances measured to a 6" spike at side center base. Bearings were measured with a hand compass (mag. delc. 20°E.) and a 6 ft. steel fence post was set within 2 ft.