

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700277

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only, T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 153)

At point of intersection, I set a post 4½ ft. long, 4" sq., 24" in the ground, for closing cor. to secs. 19 and 30, marked S19 on N.; C C T20S R11W on E.; S30 on S. faces, with 2 notches on S. and 4 notches on N. faces; from which
A Spruce 18" dia., bears N.44°E., 33 lks. dist. mkd. T20S R11W S19 BT.
A Hemlock 8" dia., bears S.66½°E., 32 lks. dist. mkd. T20S R11W S30 BT.
A Hemlock 20" dia., bears S.80°W., 22 lks. dist. mkd. T20S R11W CC S30 & 19 BT.

June 8, 1892

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

Found - Post marking corner position. (The post agrees with the closest position we can establish with the position of the BTs.)
The original 18" Spruce N.44°E., 21.78 ft. and the orig. 20" Hemlock S.80°W., 14.52 ft. are windfalls.
The SE Hemlock is apparently gone.
I reset this corner with a 1" brassed cap pipe and mark new BTs as follows:
4" Hemlock S.78°E., 10.7 ft.
4" Wester Red Cedar S.4°W., 7.8 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - June 10, 1992 - C.S. File 64/26-20

Found - 3" dia. brass cap on a 1¼" O.D. Iron pipe, protruding 12" above ground.
18" now 24" dia. uprooted and down rotting Spruce, trunk is earth covered, root hole bears N.44°E., 21.8 ft. (agrees w/rec) Orig. BT.
20" now 30" dia. uprooted and down rotting Hemlock, trunk unearthed, a blaze with illegible scribe marks found. Root hole bears S.80°W., 14.5 ft. (agrees w/rec) Orig. BT.
8" dia. Hemlock now roots found, bears S.66½°E., 21.1 ft. Orig. BT.
4" now 21" dia. Hemlock with a fully healed single blaze facing N.30°W., bears S.78°E., 10.7 ft. (agrees w/rec)

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700277

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only, T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

4" now 12" dia. R.Cedar with a fully healed single blaze, bears S.4°W., 7.1 ft. (Rec. S.4°W., 7.8 ft.)
New BTs -13" dia. Hemlock double blazed and scribed "CC T20S R1W S19 CS BT" bears N.64°E., 43.1 ft.
21" dia. D.Fir double blazed and scribed 'CC T20S R11W S30 CS BT" bears S.36°E., 13.6 ft.

Fd. ok by Troy J. Rambo - Oct. 1998 - M 131-9.