

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 113)

A Chittem tree, 12" dia., which I marked for ¼ sec. cor., ¼ S on W. face; from which
 A Spruce 14" dia., bears S.2½°W., 40 lks. dist. mkd. ¼ S BT.
 A Chittem 15" dia., bears S.32°E., 22 lks. dist. mkd. ¼ S BT.

GL0 survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 78)

Found ¼ sec. cor., which is a Chittemwood, 12" dia., marked and witnessed as described by the surveyor general, is 40 lks. W.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

Find a 1" Iron pipe, said corner being witnessed as follows:
 24" Spruce snag, S.3°W., 27.10 ft. (Orig. BT.)
I mark new trees as follows:
 32" Hemlock S.50°W., 37.10 ft.
 Schoolmarm Spruce N.52°W., 63.10 ft.

Survey by Clyde Mulkins L.S. #2008 - For: Sparrow-Pacific and Richard Holmes - Oct. 30, 1987 - M 101-31

Found - 1" Iron pipe.
 Orig. BT, Spruce stump with visible scribe marked "BT" bears S.8°W., 27.1 ft.
 Schoolmarm Spruce bears N.50°W., 63.9 ft. (Rec. N.52°W., 63.1 ft.)
 32" Hemlock stump bears S.61°W., 37.0 ft.
Set 3/4" x 30" rebar and 2" alum. cap.
New BTs -9" Fir scribed "¼ BT" bears N.75°E., 21.8 ft.
 6" D.Fir scribed "¼ BT" bears S.23½°W., 4.9 ft.

Fd. OK Sept. 1999 by T. Hostetter - M133-40