

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only (East)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 112)

An Alder 8" dia., which I marked for cor. to secs. 7, 12, 13 and 18, T20S S7 on NE.; R11W S18 on SE.; R12W S13 on SW.; S12 on NW. faces, with 2 notches on N. and 4 notches on S. sides; from which

A Fir 36" dia., bears N.51½°E., 30 lks. dist. mkd. T20S R11W S7 BT.

An Alder 9" dia., bears S.66°E., 17 lks. dist. mkd. T20S R11W S18 BT.

A Fir 36" dia., bears S.18°W., 9 lks. dist. mkd. T20S R12W S13 BT.

An Alder 8" dia., bears N.89°W., 5 lks. dist. mkd. T20S R12W S12 BT.

GLO survey by Wm. H. Byars, Deputy Surveyor, under contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 69)

The cor. of 12 and 13, on the E. bdy. of the Tp., which is an Alder 10" dia., properly marked and witnessed as per field notes furnished by the surveyor general. May 5, 1904

Fd. post & original BTs, April 1958 by Lecklider - M 8-38

Survey by Tom O. McCullough - For: U.S. Forest Service - Feb. 1970 - C.S. File 55/142-6

Found - 1" pipe and old post, from which

70" Fir bears N.51°E., 17.8 ft., old face chopped out, with tags.

40" Fir shell bears S.22°W., 6.9 ft.

Set 2" x 30" Iron pipe with brass cap mkd:

R12W	T 20 S	R11W	
12	7		
13			
	1970		
	650		

from which

18" Spruce N.18°W., 28.7 ft. scribed S12 R12 BT.

6" Spruce S.20°W., 27.6 ft. scribed S13 R12 BT.

Set 1 fence post ± 5 ft. West facing North.
Placed the 1" pipe East of corner.

Fd. OK July 1988 by D. Baker - M 106-67

continued next page

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tony Hostetter - For: Roseburg Resources Co. - Sept. 1999 -
M 133-40

Found - 2½" iron pipe & cap mkd: "LS #650 1970" & 3 BTs as
described by Baker in 1988.

New BTs- 28" Fir scribed "S13 CC BT" bears S.70°e., 31.6 ft.
to spike in root collars, below face. BT tag.
24" Fir tagged only, bears N.40°W., 14.7 ft. to
spike in root collars, below face. BT tag.
6 ft. post approx. 1 ft. south.