

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 1, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 786)

-----  
Set ¼ sec. post, from which  
A Redwood, 36" dia., bears N.43°W., 161 lks. dist.  
A Fir 12" dia., bears S.83°E., 243 lks. dist.

F.C. Frear - Wit: N.E. Richardson; B.A. Lane; J.L. Cling - Oct. 24, 1937 - (No record source given in former renewal recording)

-----  
Reset from 40" Red Cedar N.43°W., 110.2 ft. Marks plain.  
Drove 2½" x 30" auto spring, from which a  
30" W.Fir bears S.61°E., 23.5 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Clete Putnam, crew - June 21, 1961 - C.S. File 49/68-9

-----  
Found - Orig. 36" now 60" Cedar, shows good scribing on old face.  
Orig. 12" now mostly rotted Fir stump. We do find good scribing near base "T".  
Richardson's BT as recorded but do not find auto spring set for corner.

(Sketch in CS File)  
Set Brass cap at cor. mkd: County Surveyors Office, 1961 ¼ R5W S1 S6 R4W T21S  
New BT - 12" W.Fir bears N.38°W., 17.2 ft. scribed ¼ S1 CS BT

Fd. OK, Dec. 1968, V.R.T. - DCSO - C.S. File 54/14-39A  
Fd. OK, June 1990 - M 110-29