

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 6, T22-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 753)

Set ¼ sec. post, from which
 A Fir 10" dia., bears S.16°E., 45 lks. dist.
 A Fir 5" dia., bears N.15°E., 37 lks. dist.

Floyd J. Cole - For: V. Thomas and Galdabini - April 8, 1914
- Field Book 39 Page 17 (Also Vol. Book 2 Pg. 258)

Find both trees. S.16°E., cut, marks visible.
Set corner and mark 1
 A Fir 28" dia., S.10°E., 49 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - Sept. 1962 - C.S. File 49/42-62

Found - Iron bolt, 1" dia., with square head, at corner.
 36" Fir, uprooted and down, S.10°E., 32.3 ft. This tree shows an old face, now charred and with no scribing visible, which would have faced corner when tree was still standing. See affidavit in file by Mr. Glen Coons, which he swears he saw scribing on this tree while it was still standing. (Cole, 1914)
 No trace found of either original BT.
Did Not Set Brass Cap
New BTs -16" W.Fir S.32°E., 63.6 ft. mkd. ¼ S6 CS BT.
 24" D.Fir N.24°W., 34.5 ft. mkd. ¼ S31 CS BT.
Corner lies 4.5 ft. North of East and West fence line.

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18600-01)

The ¼ sec.cor., perpetuated and recorded by Floyd J. Cole, Deputy Co. Surveyor in 1914, from original evidence no longer in existence, and further perpetuated and recorded by Godfrey in 1962; monumented with an iron bolt, 1" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Godfrey:

(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 6, T22-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears S.32°E., 96 lks. dist., with a down Fir alongside, size indeterminate, no marks visible.

A Fir 33" dia., bears N.23½°W., 49 lks. dist. with healed double blaze.

and a bearing tree of no record:

A Fir 28" dia., bears S85½°W., 46 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 4 W

¼ S 31
S 6

T 22 S R 4 W

1988

from which a new bearing tree:

A Fir 6" dia., bears N.79°E., 10½ lks. dist. mkd. ¼ S31 BT.

Deposit iron bolt inside and white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK, Dec. 1994 by Les Roberts - M 121-26