

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

F.J. Cole - April 8, 1914 - Field Book 39 Page 20 and Vol. 2 Page 258

Set ¼ sec. corner in sec. 31, 19 lks. W. of random North and South through section, and 14 lks. North of random E. and W. and mark;

A Cedar 4" dia., bears N.71½°W, 31 lks.

A Fir 40" dia., bears N.32°E., 3 lks.

A Fir 36" dia., bears S.30°W., 38 lks.

A Fir 4" dia., bears S.59½°E., 38 lks.

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18615-16)

Point for the center ¼ sec. cor. of sec. 31, at intersection with the E. and W. center line.

Set a stainless steel post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 21 S R 4 W

C¼ S 31

1988

from which

A Fir 11" dia., bears N.72°E., 37 lks. dist.mkd. C¼ S11 BT

A Fir 21" dia., bears S.86½°W., 10 lks. dist. mkd. C¼ S31 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.