

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 19 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon & Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page 777)

-----  
Set ¼ sec. post, from which  
A W.Oak 8" dia., bears N.55°W., 110 lks. dist.  
A W.Oak 10" dia., bears S.34°W., 175 lks. dist.

W.F. Briggs - For: Robert Analof - Nov 3, 1891 - Vol 1 Pg 191

-----  
Set new corner marked post "¼ S CS", from which made new BTs, old ones badly decayed:  
Fir 10" dia., bears S.35½°E., 15 lks. dist.  
Fir 12" dia., bears N.40°W., 30 lks. dist.

Fd. Cor. Nov. 1901 by Oscar Thiel - Field Book 113 Pg. 107

Survey by Ralph Follett - Nov. 1950 - C.S. File 40/289

-----  
Found 5/8" bolt at N-S and W. fence corner. C.O.P.CO pole A3379 is N.0°30'W., 46.3 ft.

Survey by Bruce A. Shaner - For: Lee Kruse and Weyerhaeuser Co. - Feb. 1962 - RM 2-17

-----  
Found 5/8" Bolt at fence corner (N-S and W) as described by Follet & Ford in 1950 survey. From the bolt, N.40°W., 30 lks., I found an old rotted D.Fir stump, no scribes visible; this was a probable BT. As the bolt is close to the computed corner, I accepted it as corner, and from which  
18" D.Fir bears N.74°W., 30.2 ft. I scribed "¼S BT"  
24" D.Fir bears S.20°E., 2.8 ft. I scribed "¼S BT"

Fd. OK, Jan. 3, 1989 by L. Roberts - M 108-12- C.S. 63/85-19  
Fd. OK, July 1990 - Land Partition 1990-0034  
Fd. bolt & 2 BTs by Carl Sweeden, 5/2006 - M150-52 & M150-64 & 2006-0055

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 6/5/2006 - C.S. File 67/14-16

-----  
Found - 5/8" dia., bolt w/1¼" sq. head. Bolt lies in depression at base of SE BT.  
24" D.Fir now 47" dia. healed (rec. S.20°E., 2.8 ft)  
18" D.fir now 17" dia., x 4 ft tall rotting stump. Blaze is chopped out & scribing "¼ S BT" is visible bears N.74°W., 30.2 ft. (agrees w/rec.)  
1962 BT continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 19 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Power pole A2279 is now a rotted stub with new power pole to East. Stub bears N.0°30'W., 45.3 ft. (rec. N.0°30'W., 46.3; rec. dist could be slope dist) 1950 BO.

No trace of any other BTS of rec.

New - 11" dia., D.Fir double blazed & scribed "¼ S19 CS BT" bears N.12½°E., 14.2 ft.  
22" dia., W.Fir double blazed & scribed "¼ S19 CS BT" bears N.33¼°W., 48.6 ft.  
18" dia., Maple double blazed & scribed "¼ S30 CS BT" bears S.76½°W., 48.6 ft.

Note - Dilapidated fences run south & northeasterly from corner.  
Compass decl. 16¾°E.

Fd as per record by D. Edwards 7/2019 - M175-75