TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Charles W. Guile - For: Weyerhaeuser Co. - Nov. 17, 1986 - C.S. File 63/45(n) and M 103-9

Set 1" x 36" Iron pipe with cap mkd. "Guile PLS 472", from which
28" Fir bears N.54 3/4°E., 47.4 ft. to "W" nail "¼ WT"
16" Fir bears S.34¼°E., 31.0 ft. to "W" nail "¼ WT".

Fd. OK, Dec. 1991 by D. Peel - M 114-41

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - 10/1/2013 - C.S. File 67/40-13

Found - The orig. monument, a 1"x36" iron pipe (etc.) now a 1" I.D. iron pipe with a yellow plastic cap (properly mkd) driven into its top, is firmly set protruding 8" above ground.
28" fir now a 30" dia., 3 ft. tall D.Fir stump with a fully healed double blaze (noted "W" nail not fd); bears N.54¾°E., 48.7 ft (bearing agrees with rec., orig. dist may have been to "W" nail) OBT
No evidence of SE orig. BT.

New - 15" dia., madrone scribed "C¼ S18 CS" "BT" on a double blaze; bears N.41°E., 36.3 ft.
9" dia., D.Fir scribed "C¼ S18" "CS BT" on a double blaze; bears S.43½°E., 15.6 ft.
9" dia., D.Fir scribed "C¼ S18 CS" "BT" on a double blaze; bears S.63½°W., 9.8 ft.
5" dia., D.fir scribed "X" "CSBT" on a high-low blaze; bears N.2¾°W., 18.6 ft.
(from sketch on corner report: Forest access road is South 75' from the corner)

Note - Monument is on gentle southeast slope in forest of older reprod. fir with some maple and madrone.
Compass decl. 15½°E.