

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2762, surveyed May/June 2015 - (DCSO records Vol. 58 Page 23472-3)

-----

Point for the center ¼ sec. cor. of sec. 7 at intersection with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd.

T 21 S R 4 W  
C ¼ S 7  
2015

from which

A fir, 44" dia., bears S.30½°W., 20.9 ft., mkd. C¼ S7 BT.

A maple, 14" dia., N.35¼°W., 35.6 ft., mkd X BT in the bark.

New BTs has a 2½"x¼" magnetic nail driven at the base on right side center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum angle irons were driven alongside each monument.

From this cor., a point established in an 1980 administrative survey by Roseburg District Office, BLM, bears S.18°08'14"E., 7.084 ft., monumented with an iron pipe, 1" dia., firmly set, projecting 9" above the ground, and is not accepted as the cor. and not utilized in the course of this survey. Removed the iron pipe and deposited it inside the stainless steel post.