

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 170700

PRIMARY CORNER DESCRIPTION SE Cor. of Geo. Ozment DLC #44 (T20-4)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

**ON COUNTY LINE BE SURE TO CHECK WITH
LANE CO. SURVEYORS OFFICE**

This DLC is in T20S R4W but the SE corner is on the county line. DLC information is typed from information obtained from the Lane Co. Surveyor's Office website.

Surveys of Donation Land Claims by - J.P. Welsh, Deputy,
dated 1856

Set post

12" Fir, bears N.47°30'E., 14 lks. = 9.2'
16" Fir, bears S.23°12'W., 23 lks. = 15.2'
6" Fir, bears S.66°E., 23lk. = 15.2'

U.E. Nelson - 1937 - Lane Co. Records - C.S. 65/49-7A

Fd. SE cor. Ozment DLC (NO monument mentioned)
Set IP (This survey not recorded until 1986)
BTs - nothing mentioned.

C.C. Hayden - 1951 - Lane Co. Records - C.S. 65/49-7A

Found - 1/2" iron pipe.
30" Fir N.54°E., 9.2'
60" Fir S.33°W., 15.2'
30" Fir stump S.32°E., 15.2'

Lane Co. Surveyors Office - J. Uehlin - 1982 - Lane Co.
Records - C.S. 65/49-7A

Found - 1/2" Iron pipe.
60" fir stump, sawed into lower face & fd. scribed
"BT" Orig. Rec. from ctr. was used to set brass
cap. (Rec. S.23°12'W., 23 lks.)
All other BTs stumps Obliterated.
Set - Brass cap in 1½" O.D. iron pipe at rec. Bearing &
Distance from ctr. of orig. fir stump.
1/2" Iron pipe bears S.72°E., 2.60'
10" fir, mkd. "CSBT" N.40½°W., 58.0 to face.
8" Fir, mkd. "CSBT" N.82°E., 35.95' to face.
Note - E.H. Mitchell present when sawing into BT stump with
scribing - the 1951 BT that is noted "S.33°W." is
considered in error, as the orig. call is
"S.23°12'W."

continued next page

PRIMARY CORNER DESCRIPTION SE Cor. of Geo. Ozment DLC #44 (T20-4)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Lane Co. Surveyors Office - L. Brown - 1986 - Lane Co. Records - C.S. 65/49-7A

Found - Co. brass cap on 1" pipe.
 1/2"x16" Iron pipe 2.60' SE'ly from cap.
 60" fir stump with old scribing visible bears S.34½°W., 15.46' to center.
 9" Fir W/scribing partly visible N.78½°E., 33.8' to face & 34.2' to ctr. top of root crown. Set orange magnet on line @ 5.0' from tree center.
 11" Fir w/healed face bears N.41½°W., 60.35 to face & 60.8' to Ctr. Top o root crown, set silver magnet on line @ 5.0' from tree ctr.
 Boat spike w/1" head 1.58' SE'ly from ½" pipe as fd. No record of spike found.

Set - Moved fd. brass cap to the position of ½" I.pipe added "1986".
 Set blue magnet 6" below base of pipe.
 Wit. post & sign 1.0' So. of corner.

Note - The 1982 re-est records the finding of a 1/2" iron pipe of unknown origin. The survey by Nelson was not recorded until 1986. J. Uehlin was not aware the pipe he fd. was set by Nelson as a corner monument when he was there in 1982 . Nelson set an iron pipe in 1937 & Hayden fd a 1/2" iron pipe in 1951. In 1982 the brass cap was set @ rec. bearing & dist. from the orig. SW BT. In 1982 position differed from the position of the fd. 1/2" iron pipe & the resulting bearing & dist. from the brass cap to the 1/2" iron pipe was S.72°E., 2.60'.
 The 1/2" iron pipe & boat spike were both removed & buried alongside the re-set brass cap.

BLM dependent resurvey by Craig L. Wanless & Daniel N. Patterson, Cadastral Surveyors, under Group #1577, Surveyed April 1991/April 1993 - Filed Jan. 12, 2004 DCSO - C.S. File 65/49-8 A-I

The SE cor. of DLC #44, perpetuated by Nelson in 1937, recorded in LCSO in 1986, utilized by Hayden in 1951, subsequently perpetuated by Ezell in 1982; monumented with an iron pipe, 1" dia., firmly set, projecting 2" above ground with brass cap mkd:

LANE COUNTY
 T 20 S R 4 W
 _____ | 1982
 1986

SE DLC 44 continued next page

PRIMARY CORNER DESCRIPTION SE Cor. of Geo. Ozment DIC #44 (T20-4)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of orig. BTs
A decayed & sawed fir stump, 30" dia., bears N.57°E., 15 lks., no marks visible. (Rec. N.47½°E., 14 lks.)
A decayed & sawed fir stump, size indeterminate, bears S.33¼°W., 23 lks., no marks visible. (Rec. S.23°12'W.) and BT trees mkd. by Ezell
A fir, 11" dia., bears N.78½°E., 52 lks., with healed blaze.
A fir, 12" dia., bears N.41½°W., 92 lks., with healed blaze.

Lane Co. Surveyors Office - Murray Frazee & George Grasham -
March 4, 2003 - C.S. File 65/49-7 A-D

Found - At the cor position ds. a Lane Co. 2½" brass cap dated 1982 & 1986, firmly set & flush, on a 1½" O.D. iron pipe.
Witness sign on metal fence post south 1.0'
1856 - very rotten remains of 44"x40" high sawed fir stump w/BT tag brs. N.58°30'E., 9.2' to center (Orig. GLO rec. N.47°30'E., 14 lks. = 9.2') NE'ly portion of stump is standing & the rest is rotted nearly to the ground. No marks of axework was fd.
1856 - 60"x6' high fir stump in rotting condition bears S.33°30'W., 15.3' to center (orig. GLO rec. S.23°12'W., 23 lks. = 15.2') Stump was previously sawed & chopped into exposing part of face & scribing which we fd. as faint but definite portions of scribing that was not well preserved with pitch. Fd. 1992 BLM BT tag.
1856 - 30"x2½" high rotting fir stump brs S.34°E., 14.9' to center (orig. GLO rec. S.66°E., 23 lks. = 15.2'). A wedge shaped piece was previously sawed to stump center for scribing search. We fd. no axe work or scribing.
1982 - 14" fir with healed face & 2 BT tags bears N.42°11'40"W., 59.92' to nail we set & 60.5' to ctr (1982 rec. N.40½°W. 58.0' to face, 1986 rec. N.41½°W., 60.8' to ctr top of root crown) Added a LCSO BT tag. With metal detector got strong reading at 1986 rec, position for silver magnet.
1982 - 14" Fir with healed face & 2 BT tags bears N.79°38'30"E., 33.38' to nail we set & 34.0' to ctr (1982 rec. N.82°E., 35.95' to face) (1986 rec. N.78½°E., 34.2' to ctr top of root crown) Added a LCSO BT tag. With metal detector got strong reading at 1986 rec, position for orange magnet.

continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 170700

PRIMARY CORNER DESCRIPTION SE Cor. of Geo. Ozment DIC #44 (T20-4)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 13" Fir blazed & scribed "CSBT" brs S.47°48'E.,
27.20' to nail we set & 27.7' to center. Added
LCSO BT tag. Set a pink magnet 1' deep & on line
@ 16.8'.

12" Fir that forks 2½' above ground, blazed &
scribed "CSBT" brs S.29°42'W., 7.92' to nail we
set & 8.8' to center of 21" dia., base. Added
LCSO BT tag. Set a white magnet 1' deep & on line
@ 4.1'.

Note - Mag. dec. 17°E.

Basis of Bearing -

Solar observation using the hour-angle method.

Geographic Map location -

For navigation to corner area - not of survey grade
accuracy

NAD 83/91 Values = Lat: N 43°46'46.0"

Long: W 123°12'34.6"

BTs - Dist. to nail refers to a Mag nail & brass washer
driven into the bottom of the face of new BTs or
near the base of tree & facing the corner
position in fd. BTs.

Equipment used -

TOPCON GTS-301 total station; HP-48 GX data collector

**ON COUNTY LINE BE SURE TO CHECK WITH
LANE CO. SURVEYORS OFFICE**