

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 774)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.15°E., 50 lks. dist.
A Hemlock 10" dia., bears N.36°W., 29 lks. dist.

F.J. Cole - For: Thomas and Goldabini - April 1914 - Vol. 2 Page 258

No evidence of original corner. Set Cedar post, from which
A Fir 10" dia., S.29½°E., 101 lks.
Hemlock 7" dia., S.71°W., 91 lks.
A Cedar 24" dia., N.19¼°E., 140 lks.

Wilford N. Haines - For: Glenn (?) - Nov. 1962 - C.S. File 51/247-1 & 3 and H-65

Found - 10" Fir S.29½°E., 101 lks., now stump.
24" Cedar N.18°E., 104.6 ft. (not 140 lks.) now stump.
Set 1" x 1" x 36" T. Iron by using bearing and dist. to 10" Fir and bearing only to 24" Cedar, scribed 2 new BTs:
8" Fir S.30°E., 38.3 ft. scribed, alive & standing.
8" Fir N.53°W., 31.7 ft. uprooted & down, probably blown over in Oct. 1962 storm.
NOTE BY MILO GODFREY: My point for corner, assuming 20 lks. error in Cole's notes, falls S.85°W., 1.8 ft. from Haines' "T" iron. April 23, 1963. See notes in C.S. File 51/247

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18604)

The ¼ sec. cor., reestablished and recorded by Cole in 1914, and perpetuated and recorded by Haines in 1962. There is no remaining evidence of the original corner, and this position is accepted as the corner; monumented with "T" shaped iron rod, 1" dia., firmly set, projecting 10" above ground, from which the remains of bearing trees mkd. by Cole:
A sawed Cedar stump 25" dia., bears N.18°E., 159 lks. dist., no marks visible.
A sawed Fir stump 18" dia., bears S.28°E., 100 lks. dist., no marks visible.
(Cont. Next Page)

