

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 774)

-----  
Set post cor. of secs. 29, 30, 31 and 32, from which  
A Fir 10" dia., bears S.79°E., 27 lks. dist.  
A Fir 6" dia., bears S.5°W., 31 lks. dist.  
A Cedar 20" dia., bears N.25°E., 49 lks. dist.  
A Maple 10" dia., bears N.23°W., 27 lks. dist.

F.J.Cole - For: Thomas & Galdobini - April 1914 - Field Book (?) Pg. 17 and Vol. 2 Pg. 258

-----  
Find Maple stump Iron pin in place for corner.

Wilford N. Haines - 1962 - C.S. File 51/247-1 and H-65

-----  
Found Iron rod that has been used for corner for many years and must be the one used by Cole in 1914.

Douglas County Surveyors Office - Milo Godfrey and crew - C.S. File 49/68-12 - Oct. 1964

-----  
Corner searched for, not found.

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18604-05)

-----  
The Sec. Cor., restored by person(s) unknown, recorded by Cole in 1914, and further recorded by Haines in 1962. There is no remaining original evidence of the corner, and this position is accepted as the corner; monumented with an iron rod, 3/4" dia., firmly set, projecting 4" above ground, with an iron pipe alongside, 1 1/4" dia., firmly set, buried 14" below surface of ground.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 4 W  
S 30 | S 29  
S 31 | S 32  
1988

from which  
(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Maple 21" dia., bears N.78°E., 66 lks. dist., mkd. T21S R4W S29 BT.  
A Fir 11" dia., bears S.3½°E., 98 lks. dist., mkd. X BT.  
A Maple 25" dia., bears N.78½°W., 100 lks. dist., mkd. T21S R4W S30 BT.  
Deposit the iron pipe and iron rod inside and white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Ok by Gerald Riley, 12/1994, M 130-16  
Fd. OK by M. Heimburger, Nov. 1999 - M133-69  
Fd. Ok by David Edwards, Dec. 2000 - C.S. File 65/34-3  
Fd. BC & 3 BTs by C. Sweeden, 5/2006 - M150-52 & M150-64 & 2006-0055