

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 775)

Set ¼ sec. post, from which
A Fir 6" dia., bears N.85°E., 33 lks. dist.
A Fir 8" dia., bears S.64°W., 27 lks. dist.

F.J. Cole, Deputy - Wit: S.S. Thomas; Joe Goldabini - April 1914 - Vol. 2 Pg. 258 (and "old" cor. book, Pg. 9)

Renew corner from remains of original trees, from which
A Cedar 8" dia., N.62½°W., 72 lks.
A Cedar 40" dia., N.81½°E., 102 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 49/68-11

Found - I. Cedar, now 32", N.62½°W., 47.5 ft., opened and found fragmentary but unmistakable scribing, on badly, rotted old face.

Did not find Cole's other BT, nor other Orig. BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 4 W
¼ S30 | S29
1964

New BTs- 9" D. Fir S.64°E., 22.8 ft. mkd. ¼ S29 CS BT.
13" W. Fir S.64°W., 12.4 ft. mkd. ¼ S30 CS BT.
Fence corner, fences N., S., & W., bears N.52°E., 5.0 ft.

Carl Sweeden - For: ODOT - May 2006 - M150-52 & M150-64

Found - Brass cap, up 0.5', leaning slightly
13" W. Fir now 20", S.64°W., 12.4', healed, tag.
No trace of S.64°E., BT, road in area.
New BTs- 5" W. Fir, N.18°W., 8.9', tagged, scribed "X BT"
6" W. Fir, N.19°E., 9.2', tagged, scribed "X BT"
5" D. Fir, S.58°E., 9.6', tagged, scribed "X BT"

Fd as per record by D. Edwards 7/2019 - M175-75
Fd. OK per rec. by M. Wyntergreen - 11/2020 - M178-16 A-B