

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 779)

Set post cor. of secs. 7, 8, 17 and 18, from which

- A Fir 30" dia., bears S.20°W., 19 lks. dist.
- A Fir 10" dia., bears S.87°E., 44 lks. dist.
- A Fir 6" dia., bears N.60°W., 76 lks. dist.
- A Dogwood 7" dia., bears N.31°E., 90 lks. dist.

C.W. Springer, Deputy Co. Surveyor - Wit: Bergh; Roy Beebe; L. Watkins; J. Watkins - Feb. 1923 - Field Book 60 Pg. 66 (and "old" cor. book, Pg. 9)

Renewed corner from 2 original BTs which were alive and standing. Other two trees rotted away and fallen. One still had plain scribe marks visible.

Set a 3" x 3" x 36" Cedar post, from which

- Orig. BT, Fir 36" dia., bears S.20°W., 12.5 ft.
- New BT, Fir 40" dia., N.72°20'E., 56.6 ft.
- New BT, 48" Fir, N.77°40'E., 56.6 ft.
- New BT, 48" Fir, S.67°30'E., 63 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April 1969 - C.S. File 54/14-29

Found - Unrecorded 1" x 1" I. Bolt.

- Orig. 30" now 53" Fir, alive, S.20°W., 12.5 ft., previously opened, face burned.
- 40" Fir, down, burned, badly decayed, N.72°20'E., 56.6 ft.
- 48" Fir, now sawed stump, S.67°30'E., 63.0 ft., scribe visible on unhealed blaze, partly burned.

No trace other bearing tree called for in renewal.

Set Brass cap at cor. mkd: County Surveyors Office
(Reset bolt alongside brass cap)

T 21 S R 4 W			
S	7		S 8
S	18		S 17

1969

New BTs-

- 10" D.Fir N.44°E., 21.0 ft. mkd. T21S R4W S8 CS BT.
- 9" D.Fir S.33°E., 17.7 ft. mkd. T21S R4W S17 CS BT.
- 8" D.Fir S.85°W., 7.8 ft. mkd. T21S R4W S18 CS BT.
- 8" D.Fir N.74°W., 9.6 ft. mkd. T21S R4W S7 CS BT.

Corner lies on moderate easterly slope in dense D.Fir reproduction, logging estimated about 1920 to 1930.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. and used in BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15023-24)

Survey by Charles Guile - For: Weyerhaeuser Co. - Nov. 17. 1986 - C.S. File 63/45(n) and M 103-9

Found - DCSO 1969 brass cap.
10" Fir bears S.34°E., 17.5 ft.
50" Fir bears S.23°W., 13.3 ft.
8" Fir bears S.86°W., 7.8 ft.
9" Fir bears N.72½°W., 9.7 ft.
New BT - 10" Fir bears N.74°E., 28.2 f. to "W" nail, "Sec. 8 BT"

Fd. OK, May 1996 by Bradsby - M 123-76

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - June 21, 2013 - C.S. File 67/38-35

Found - A (1969) 2½" dia., brass cap (properly mkd) on a 1" I.D. iron pipe, firmly & plumbly set, protruding 12" above ground.
An unrecorded iron bolt with 1"x1" sq. top is set flush with ground on the SW'ly edge of the BC monument.
A fir 30" dia., now a 50" dia., 8 ft. tall fir stump with blaze no longer discernible; bears S.23°W., 13.3 ft. (agrees w/1986 rec.) OBT
A 48" Fir, now 48" dia., 4 ft. tall rotted fir stump with no face or scribing remaining; bears S.67½°E., 63.0 ft. (As per rec.) 1923
A 10" D.Fir now a rotted nearly flush w/ground fir stump; bears N.44°E., 21.0 ft (as per rec.) 1969
A 9" D.Fir now a 13" dia., 2 ft. tall D.Fir stump with a previously opened blaze showing the scribing "B"; bears S.34°E., 17.5 ft. (agrees w/1986 rec.) 1969
An 8" D.Fir, now an 8" dia., 1½ ft. tall rotted fir stump with possible blaze evidence bears S.86°W., 7.8 ft. (agrees with 1986 rec.) 1969
An 8" D.Fir, now an 10" dia 2 ft tall rotted fir stump w/possible blaze evidence bears N.72½°W. 9.6 ft (bearing per 1986 rec.; dist per 1969 rec)
A 10" fir, now a 14" dia., 1 ft. tall rotted fir stump with no blaze or scribe marks but still holding a "W" nail; bears N.74°E., 28.2 ft. (as per rec.) 1968

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - An 8" dia., W.Fir scribed "T21S R4W S17 CS" "BT" on a double blaze; bears S.77¾°E., 46.4 ft.
A 14" dia., maple scribed "T21S R4W S17 CS" "BT" on a double blaze; bears S.7½°E., 25.6 ft.
A double trunked maple 7" in dia., (the larger and most southerly trunk) scribed "T21S R4W S7 CS" "BT" on a double blaze; bears N.26½°W., 52.4 ft.

Note - Monument is in NW corner of older clear cut on East edge of very old second growth forest of fir, maple and dogwood.
Monument is approx. 65 ft. north of un-maintained spur road and approx. 130 ft. east of graveled forest access road.
Compass decl. 15½°E.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2762, surveyed May/June 2015 - (DCSO records Vol. 58 Page 23467-8)

The cor. of secs. 7, 8, 17, & 18, perpetuated by Guile, in 1986, further perpetuated by Smith, Douglas Co Surveyor, in 2013, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground (alongside of which is an unrecorded iron bolt, 5/8" dia., firmly set, flush with the ground, as reported by Smith) with brass cap (properly) mkd. from which the remains of an original bearing tree reported by Peterson and Berry in 1971-72

A fir stump, 50" dia., bears S.20°W., 12.5 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Springer, in 1923, reported by Peterson and Berry

A decayed fir stump, 54" dia., S.67½°E., 63.4 ft., with no marks visible.

and the remains of the bearing trees mkd. by the Douglas Co Surveyor's Office in 1969, reported by Peterson and Berry

A fir stump, 14" dia., bears S.34°E., 17.8 ft., with no marks visible.

A decayed fir stump, 8" dia., bears S.85°W., 7.9 ft., with no marks visible.

A decayed fir stump, 12" dia., bears N.74°W., 9.9 ft., with no marks visible.

and the bearing trees mkd. by Smith

A fir, 9" dia., bears S.77¾°E., 46.6 ft., with scribe marks T21S R4W S17 CS BT visible on a partially healed double blaze.

A maple, 15" dia., bears S.8°E., 26.0 ft., with scribe marks T21S R4W S17 CS BT visible on a partially healed double blaze.

continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A twin trunked maple, 7" dia., bears N.26 $\frac{3}{4}$ °W., 52.4 ft., with scribe marks T21S R4W S17 CS BT visible on a partially healed double blaze.
The geographic position in NAD 1983 (2011)
Latitude: 43°45'02.125"N. Longitude: 123°12'27.493"W.