

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 780)

Set post cor. of secs. 5, 6, 7 and 8, from which
A Fir 8" dia., bears N.27°E., 54 lks. dist.
A Fir 8" dia., bears N.20°W., 31 lks. dist.
A Fir 10" dia., bears S.62°W., 25 lks. dist.
A Fir 10" dia., bears S.70°E., 20 lks. dist.

Douglas Co. Surveyors Office - James Byron and crew - Spring 1969 - C.S. File 54/14

Looked for, not found.

BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15026)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 21 S R 4 W
S 6 | S 5
S 7 | S 8
1972

from which
A Fir 10" dia., bears N.7°E., 8 lks. mkd. T21S R4W S5 BT.
A Fir 13" dia., bears S.77°E., 29 lks mkd. T21S R4W S8 BT.
A Fir 10" dia., bears S.15°W., 20 lks mkd. T21S R4W S7 BT.
A Fir 8" dia., bears N.8°W., 16 lks. mkd. T21S R4W S6 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2762, surveyed May/June 2015 - (DCSO records Vol. 58 Page 23471-2)

The cor. of secs. 5, 6, 7, & 8, monumented with an iron post, 2½" dia., firmly set projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Peterson and Berry in 1971-72
A fir, 15" dia., bears N.7°E., 5.3 ft., with a healed blaze.
A fir stump, 18" dia., S.77°E., 19.1 ft., with a healed blaze.
A fir, 28" dia., bears S.15°W., 13.2 ft., with a healed blaze.

continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears N.83°W., 10.6 ft., with fallen fir trunk, 22" dia., lying alongside, with a healed blaze. and a new bearing tree

A fir, 9" dia., bears S.79½°W., 17.8 ft., mkd. T21S R4W S7 BT.

There are no suitable accessories available in secs. 6 or 8.

Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description. Aluminum angle irons were driven alongside each monument unless a similar marker was already in place.