

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 774)

Set ¼ sec. post, from which
A Fir 4" dia., bears S.66°W., 82 lks. dist.
A Fir 6" dia., bears N.47°W., 54 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 49/68-19

Found - Orig., badly rotted Fir stump, N.47°W., 35.6 ft., faint scribing "BT" on old face.
No trace of SW. tree.

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 4 W
¼ $\frac{S\ 29}{S\ 32}$
1964

New BTs- 11" W.Fir S.80°W., 43.0 ft. mkd. ¼ S32 CS BT.
18" D.Fir N.2½°W., 41.4 ft. mkd. ¼ S29 CS BT.
Fence corner, fences N. & W., bears S.19°W., 24.0 ft.

Fd. OK, May. 2000 by Les Roberts - M134-76
Fd. OK per rec. by M. Wyntergreen - 11/2020 - M178-16 A-B