

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18610-11)

Set a stainless steel post 28" long, 2p" dia., 24" in the ground with brass cap mkd: T 21 S R 4 W
C¹/₄ S17
1988

from which

A Fir 11" dia., bears N.29°E., 28 lks. mkd. C¹/₄ S17 BT.

A Fir 33" dia., bears S.67°W., 52 lks. mkd. C¹/₄ S17 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

A fence corner bears N.27¹/₄°E., 0.70 chs. fence extends N & E.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- July 18, 2013 - C.S. File 67/38-43

Found - A 3¹/₄" dia., brass cap (properly mkd) on a 2¹/₂" I.D. steel pipe, protruding 4" above ground.

A fir 11" dia., now a dead and partly rotted 11" dia., approx. 30 ft. tall fir snag with a partially healed but rotted blaze (no face or scribing remains)' bears N.29°E., 18.5 ft. (as per rec) 1988

A fir 33" dia., now a 38" dia., D.Fir with a fully healed double blaze; bears S.67°W., 34.3 ft. (as per record) 1988

A fence corner now a fence corner post with bracing posts (fences are down) bears N.27¹/₄°E., 48.5 ft. (rec. N.27¹/₄°E., 46.2 ft.) 1988

New - A 15" dia. W.Fir scribed "C¹/₄ S17" "CS BT" on a double blaze; bears N.56°E., 4.7 ft.

A 12" dia., W.Fir scribed "C¹/₄ S17 CS" "BT" on a double blaze; bears S.75¹/₄°E., 17.8 ft.

A 6" dia., D.Fir scribed "C¹/₄ S17 CS" "BT" on a double blaze; bears N.51¹/₂°W., 28.8 ft.

Note - Monument is on moderate NE'ly slope in mixed fir reprod and brush. Monument is about 75 ft. east from a forest access rd.

Compass decl. 15¹/₂°E.