

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T20-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 750)

Set ¼ sec. post, from which
A R.Fir 4" dia., bears N.65°E., 8 lks. dist.
A R.Fir 30" dia., bears S.35°E., 19 lks. dist.

BLM Resurvey by Floyd Brooks; Gordon Popken; Gary Oviatt; Timothy Kent, Cadastral Surveyors, Under Group #724, Surveyed Aug. 1970 - (DCSO records Vol. 37 Page(s) 15280-81)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 20 S R 4 W
¼ S 32
 S 5

1971 from which
A Fir 10" dia., bears N.23½°E., 15½ lks. mkd. ¼ S32 BT.
A Fir 11" dia., bears S.18½°W., 22½ lks. mkd. ¼ S35 BT.

Lane Co. Surveyor's Office Mikeal Blomme' - Crew: Bruce Bothel & Stuart Duce - 2/16/2016 - C.S. File 65/111-47

Found - A 2½" iron post with 3¼" BLM brass cap (properly mkd), 4" above grade.

1971 - 23" Fir w/healed face N.23½°E., 10.3' to CTR
1971 - 26" Fir w/healed face S.18½°W., 13.9' to CTR
New - 19" Fir mkd: "CSBT" N.73½°E., 7.2' to CTR
 12" Fir mkd: "CSBT" N.84°W., 10.9' to CTR

Note - Distance shown is to an aluminum nail set at side/center of live trees.

Basis of bearing: S.18½°W., based between the ¼ corner brass cap and 1971 (SWBT).

Geographic map location: for finding the corner area - not of survey grade accuracy NAD 83/91 values:

LAT: N 43°46'46.0" LONG: W 123°11'50.0"

Equipment used: w/k compass #23157 and steel tape.

Mag dec = 15° E.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor under Group No. 2921, surveyed May 2018/Feb. 2019 - (DCSO records Vol. 59 Page(s) 24090)

The ¼ sec. cor. of secs. 5 & 32, reported by Brooks et al. in 1970-71; perpetuated by Blomme', in 2016; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. Continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T20-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the bearing trees reported by Brooks et al.
A fir, 24" dia., bears N.23½°E., 10.2 ft., with a healed blaze.
A fir, 30" dia., bears S.18½°W., 14.9 ft., with a healed blaze.
and the remains of the BTs mkd. by Blomme'
A fir, 22" dia., bears N.76½°E., 6.8 ft., with a healed blaze.
A fir snag, 12" dia., bears N.83½°W., 11.0 ft., with a healed blaze.