

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 768)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.37°W., 37 lks. dist.  
A Fir 10" dia., bears S.80°E., 41 lks. dist.

W.F. Briggs - Wit: Pet Matchatte and S. tonalee - March 16-18, 1901 - Vol. 2 Pg. 263 and Pg. 107

-----  
The original BT destroyed by fire.  
Set new post 4" x 4" square, 3½ ft. long, from which  
6" Fir bears N.48°E., 10 lks.  
40" Fir bears S.33°E., 9 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 49/68-16

-----  
Found - 28" Fir N.48°E., 6.6 ft., cut open and found good scribing "3 CS".  
Old Fir stump S.33°W., 5.9 ft., no marks found, bark gone on NE. face.

Set Brass cap at cor. mkd: County Surveyors Office  
T 21 S R 4 W  
¼ S 32 | S 33  
1964

New BTs- 9" Red Cedar N.73°E., 15.3 ft. mkd. ¼ S33 CS BT.  
10" D.Fir S.78°W., 39.6 ft. mkd. ¼ S32 CS BT.  
Corner is in 3-way fence corner, fences E., W., and N.

Cor. Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1026, surveyed July 1980/March 1981 - (DCSO records Vol. 44 Page(s) 16965-66)

David Wellman - For: Summerwood Inc. - June 1999 - M 132-12

-----  
Found - Douglas County brass cap dated 1964, 1.2 ft. above ground, cap is rotated 180 degrees.  
38" Fir N.54°E., 7.8 ft. to spike set side center - closed face - rec: N.48°E., 10 lks., 1901 Briggs  
Rotten Fir stump, S.31°W., 9.3 ft. to center - rec: S.33°E., 9 lks. 1901 Briggs.  
14" Cedar, N.75°E., 15.9 ft. to spike set side center - closed face - rec: N.73°E., 15.3 ft., 1964 Douglas Co.

continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	18" Fir stump S.77°W., 38.8 ft. to spike set side center - closed face - rec: S.78°W., 39.6 ft. 1964 Douglas Co.
Set -	12" Fir, S.42°E., 27.9 ft. to spike set side center scribed "¼ S33 BT"
	6" Fir, N.54½°W., 22.2 ft. to nail set side center scribed "X BT"
Note -	Corner lies 1.5 ft. Southwest of North/East/West fence corner.

Found OK by D. Wellman, Oct. 1999 - M133-46 Fd. as per M132-12 by D. Edwards, 10/2013 M167-4
---

--