

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 770)

Set post cor. of secs. 16, 17, 20 and 21, from which
A Fir 6" dia., bears N.67°W., 117 lks. dist.
A Fir 6" dia., bears N.40°E., 29 lks. dist.
A Fir 4" dia., bears S.15°E., 30 lks. dist.
A Fir 4" dia., bears S.19°W., 63 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Nov. 1964 - C.S. File 49/68-25

Found - 36" Fir S.15°E., 19.8 ft., opened and found good scribing "S".
Rotten remains of Fir stump, S.19°W., 41.6 ft.
No trace of NE. or NW. BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S R 4 W
S 17 | S 16
S 20 | S 21
1964

New BTs- 7" D.Fir S.43¼°W., 25.7 ft. mkd. T21S R4W S20 CS BT
14" D.Fir S.8°W., 60.5 ft. mkd. T21S R4W S21 CS BT.
20" D.Fir N.55°W., 45.5 ft. mkd. T21S R4W S17 CS BT
42" D.Fir N.31°E., 59.0 ft. mkd. T21S R4W S16 CS BT.
Corner is in E. and W. fence line 2 ft. West of fence corner.

Cor. Fd. and used in BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 - (DCSO records Vol. 36 Page(s) 15018)

Fd. OK, April 1987 by D. Peel - M 104-12 and M 105-50

BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18607)

The Sec. Cor. monumented with an iron post 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1964, from which the remains of an original bearing tree
A sawed Fir stump 47" dia., bears S.15°E., 30 lks. dist., with fragmentary scribe marks visible on opened blaze.
(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Godfrey in 1964
A Fir 48" dia., bears N.31°E., 88 lks. dist. with healed
blaze. (Rec. N.41°E., 92 lks.)
A sawed Fir stump 16" dia., bears S.7½°E., 92 lks. dist.,
with healed blaze.
A Fir 9" dia., bears S.42½°W., 39 lks. dist., with healed
face.
A Fir 21" dia., bears N.55°W., 69 lks. dist., with healed
face.
and a new bearing tree
A Fir 12" dia., bears S.84°E., 47 lks. dist. mkd. T21S R4W
S21 BT.

Fd. OK, Dec. 1991 by L. Roberts - M 115-33
FD. Ok by Kris DeGroot 10/2006 - M146-46A