

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 771)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears S.55°E., 97 lks. dist.  
A Fir 15" dia., bears S.41°W., 48 lks. dist.

O.F. Thiel - For: Roy Beebe - June 9, 1924 - Field Book 115 Pg. 156

-----  
Old post in place set for survey of C.C. Watkins. NW. tree fallen, SE. tree, Cedar remarked.

BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15019)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  
T 21 S R 4 W  
1/4  
S 17 S 16  
1972

from which  
A Fir 13" dia., bears N.25°E., 57 lks. dist. mkd. ¼ S16 BT  
A Fir 10" dia., bears N.15°W., 88 lks. dist. mkd. ¼ S17 BT

Fd. and used in BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18611)

Found OK by D. Edwards, Oct. 1998 - M130-42