

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 772)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.43°W., 34 lks. dist.
A Laurel 10" dia., bears N.55°E., 44 lks. dist.

C.W. Springer, Deputy Co. Surveyor - Wit: Bergh; Beebe; L. Watkins and J. Watkins - Feb. 1923 - Field Book 60 Page 66

Found old stake marked ¼ sec. and one tree with old blaze. Renewed from evidence with a Cedar stake 3" x 3" x 36" and marked new trees:
Fir 36" dia., N.43°W., 22.4 ft.
Fir 36" dia., S.57°E., 70.1 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew with Tom Watts, BLM - - C.S. File 54/14-23

Found - 2" Iron pipe, unrecorded and BTs as recorded.
36" Fir, now badly rotted stump N.43°W., 22.4 ft. previously opened and shows "BT" scribe.
36" now 46" Fir S.57°E., 70.1 ft., now burned stump, possible fragmentary scribe on burned faces. Someone chopped an "X" on lower face.
Did Not Set Brass Cap.
New BTs- 8" Chinquapin, West 3.0 ft. mkd. ¼ S8 CS BT.
13" D.Fir S.26°E., 30.7 ft. mkd. ¼ S9 CS BT.
Corner lies 50 ft. West of very old logging road, course N-S.

BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15020-21)

The ¼ sec. cor., perpetuated by Springer in 1923, subsequently perpetuated by Tracy in 1966, monumented with an iron pipe, 2" dia., firmly set, protruding 14" above ground, from which the remains of the original bearing trees:
A sawed Fir stump 36" dia., bears N.43°W., 34 lks. dist., with scribe marks BT visible on opened blaze.
and a bearing tree mkd. by Springer:
A sawed Fir stump 46" dia., bears S.57°E., 106 lks. dist., with scribe mark X visible on opened blaze.
and bearing trees mkd. by Tracy:
A Fir 15" dia., bears S.26°E., 46 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Chinquapin 9" dia., bears West, 5 lks. dist., with scribe marks $\frac{1}{4}$ S8 CS BT visible on partially healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 4 W
1/4
S 8 | S 9
1972

Deposit iron pipe alongside the iron post.

Fd. OK, May 1996 by Bradsby - M 123-76

Found OK by D. Edwards, June 2002 - CS 65/41-6