

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 772-73)

Set post cor. of secs. 4, 5, 8 and 9, from which

- A Fir 12" dia., bears S.12°E., 17 lks. dist.
- A Fir 15" dia., bears N.73°W., 28 lks. dist.
- A Fir 10" dia., bears N.15°E., 30 lks. dist.
- A Maple 7" dia., bears S.14°W., 27 lks. dist.

Glen McChesney - For: Weyerhaeuser Co. - Nov. 1959 - C.S. File 53/104-2

Found - 10" Fir N.15°E., 19.8 ft., gone.
 12" Fir S.12°E., 11.2 ft., now 16" Fir stump 12 ft. high. Upper face, open and badly burned. Scribing visible. Chopped out lower scr and found "BT" scribing.
 7" Maple S.14°W., 17.8 ft., gone.
 15" Fir N.73°W., 18.5 ft., found stump hole and 24" Fir slid 15 ft. downhill.

Set 10" x 10" x 18" Basalt stone.

New BTs- 10" Fir N.27°E., 32.9 ft. added "W" nail & plate.
 3" Fir S.29°E., 9.6 ft. added "W" nail & plate.
 6" Fir N.6°W., 21.3 ft. added "W" nail & plate.
 10" Fir N.74°W., 16.2 ft. added "W" nail & plate.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew with Tom Watts, BLM - July 26, 1966 - C.S. File 54/14-25

Found - Sandstone 10"x10"x18", firmly set, recorded as basalt.
 Orig. 12" now 16" Fir S.12°E., 11.2 ft., frag. scribe on upper scar, now burned. "BT" scribe visible on previously opened lower scar.
 Weyerhaeuser BTs alive and in good condition.

Set Brass cap at cor. mkd: County Surveyors Office

T	21	S	R	4	W
	S	5	S	4	
	S	8	S	9	
					1966

Mark existing Weyerhaeuser BTs:

- 6" D.Fir S.29°E., 9.6 ft. mkd. "T21S R4W S9 CS BT."
- 12" D.Fir N.27°E., 32.9 ft. mkd. "T21S R4W S4 CSBT"
- 9" D.Fir N.6°W., 21.3 ft. mkd. "T21S R4W S5 CS BT"
- 8" Laurel S.47°W., 26.4 ft. mkd. "T21S R4W S8 CSBT"

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. Fd. and used in BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15026-27)

Fd. OK, April 1990 by D. Peel - M 110-2

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor under Group No. 2921, surveyed May 2018/Feb. 2019 - (DCSO records Vol. 59 Page(s) 24094-5)

The cor. of secs. 4, 5, 8, & 9, reported by Peterson and Berry in 1971-72; utilized by Peel, in 1990; monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground, (alongside of which is the original basalt stone, 10x10x18" (Record: 14x10x19"), no visible marks with a brass cap (properly) mkd.
from which the remains of the BTs reported by Peterson and Berry
A decayed fir stump, 19" dia., bears N.28°E., 33.6 ft., with a healed blaze. (Record, 35.6 ft.)
A fir, 15" dia., bears S.30°E., 9.6 ft., with a healed blaze. (Record, 8.6 ft.)
A madrone, 12" dia., bears S.47°W., 27.7 ft., with a healed blaze.
and the BT by person(s) unknown, reported by Peel
A fir, 28" dia., bears N.71¼°W., 15.9 ft., with a healed blaze.
and a new BT
A fir, 14" dia., bears N.15½°E., 21.9 ft., mkd. T21 S R4W S4 BT.
Lat: 43°45'53.59" N Long: 123°11'15.88" W