

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 773)

Set ¼ sec. post, from which
A Fir 20" dia., bears N.70°W., 62 lks. dist.
A Fir 8" dia., bears S.73°E., 47 lks. dist.

Survey by Donald Peel, LS #752 - For: Weyerhaeuser Co. - April 1990 - M 110-2

Set 2" x 41" Iron pipe with brass cap, from which
17" Fir bears N.38°E., 17.6 ft. scribed ¼ S4 BT.
18" Fir bears S.56°E., 33.3 ft. scribed ¼ S4 BT.
15" Fir bears N.85°W., 16.3 ft. scribed ¼ S4 BT.
22" Fir bears N.12¼°W., 44.9 ft.
Set 6 ft. steel fence post 2 ft. North.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor under Group No. 2921, surveyed May 2018/Feb. 2019 - (DCSO records Vol. 59 Page(s) 24095)

The ¼ sec. cor. of secs, 4 & 5, reestablished by proportionate measurement by Peel, in 1990. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of the BTs mkd. by Peel
A fir, 27" dia., bears N.37°E., 18.4 ft., with a healed blaze.
A fir, 23" dia., bears N.84½°W., 17.2 ft., with a healed blaze.
A fir, 31" dia., bears N.12¼°W., 46.7 ft., with a healed blaze.