

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T20-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 748)

Set post cor. of secs. 4, 5, 32 and 33, from which
A R.Fir 50" dia., bears N.70°E., 25 lks. dist.
A R.Fir 10" dia., bears S.58°W., 83 lks. dist.
A Hemlock 18" dia., bears N.60°W., 69 lks. dist.
A Redwood 12" dia, bears S.60°E., 64 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
March 21, 1969 - C.S. File 54/14-31

Found - Orig. 50" R.Fir now 52" stump, N.70°E., 16.5 ft., shows no face or scribe, good bearing & distance.
Orig. 10" R.Fir now 16" stob, S.58°W., 54.8 ft., has been opened & shows scribe, fragmentary scribing on upper & lower faces, shows to be right age by approx. ring count.
Orig. 12" Cedar now 16" windfall, S.60°E., 42.2 ft., opened & found scribe "W 4" and show to be right age by approx. ring count.

Set Brass cap at cor. mkd: County Surveyors Office

T20S R4W S 32 | S 33
T21S R4W S 5 | S 4

1969

New BTs- 10" Chinquapin N.24°E., 21.1 ft. scribed T20S R4W S33 DCS BT.

12" D.Fir N.54°W., 28.9 ft. mkd. T20S R4W S32 DCS BT.

12" Chinquapin S.57°W., 47.2 ft. mkd. T21S R4W S5 DCS BT.

12" D.Fir S.79°E., 47.9 ft. scribed T21S R4W S4 DCS BT.

"W" nails in all new bearing trees. This corner lies on East slope.

Fd. and used in BLM Resurvey by Floyd Brooks; Gordon Popken; Gary Oviatt; Timothy Kent, Cadastral Surveyors, Under Group #724, Surveyed Aug. 1970 - (DCSO records Vol. 37 Page(s) 15280)

Fd. OK, April 1990 by Peel - M 110-2

Fd. OK, Jan. 1991 - M 111-62

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Fd. OK, April 1990 by Peel - M 110-2 (1971 BLM BC)</p>
<p>Lane Co. Surveyor's Office Mikeal Blomme' - Crew: Bruce Bothel & Stuart Duce - 2/25/2016 - C.S. File 65/111-48</p> <p>-----</p> <p>Found - A 2½ DCS0 brass cap atop a 1½" iron post, 6" above surface.</p> <p>1854 - A 50" leaning and rotten fir stump brs N.63°E., 17.5' to approx CTR (N.70°E., 16.5').</p> <p>1959 - Remains of 12" Chin. stump with offspring brs N.23°E., 22.3' to CTR (N.24°E. 22.1' TO "W" nail)</p> <p>1959 - A 19"x6' rotten fir stump w/healed face brs N.53°W., 29.1' to CTR (N.54°W. 28.9' TO "W" nail)</p> <p>1959 - 27' D.Fir w/healed face S.79°55'E. 48.0' to CTR</p> <p>1959 - 22" D.Fir w/healed face S.57°W., 46.4' to "W" nail, 47.5' to CTR</p> <p>New - 22" D.Fir "CSBT" N.22°25'E., 34.2' to CTR</p> <p>5/8"x30" rebar w/2" alum cap "LCS0-RP1-2016" 4" below surface N.68°34'W., 19.00'</p> <p>Note - Distance shown is to an aluminum nail set at side/center of live trees.</p> <p>Basis of bearing: S.57°W. from brass cap to 1959 (SWBT).</p> <p>Geographic map location: not of survey grade accuracy NAD 83/91 values: LAT: N 43°46'46.2' LONG: W 123°11'14.1'</p> <p>Equipment used: LEICA TCR 1203 & SPECTRA PRECISION RANGER DATA COLLECTOR.</p>
<p>BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor under Group No. 2921, surveyed May 2018/Feb. 2019 - (DCS0 records Vol. 59 Page(s) 24089-90)</p> <p>-----</p> <p>The cor. of secs. 4, 5, 32, and 33, reported by Brooks at al. in 1970-71; perpetuated by, Blomme', in 2016; monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.</p> <p>from which the remains of the BTs reported by Brooks et al.</p> <p>A decayed fir stump, 34" dia., bears N.70°E., 16.5 ft., no marks visible. (Original)</p> <p>A fir, 30" dia., bears S.79°E., 47.5 ft., with a healed blaze and an aluminum nail right side center.</p> <p>A fir, 24" dia., bears S.57°W., 47.5 ft., with a healed blaze.</p> <p>A fir stump, 18" dia., bears N.54°W., 28.7 ft., no marks visible.</p> <p>and the accessories established by Blomme'</p> <p>A fir, 23" dia., bears N.23½°E., 34.0 ft., with a healed blaze.</p> <p>An iron rod, 5/8" dia., firmly set, with top 4" below the surface of the ground, bears N.67°08'53" W., 18.97 ft. with an aluminum cap mkd. LCS0 RP1 2016.</p> <p>Lat: 43°46'46.63"N Long: 123°10'02.11"W NAD 1983 (2011)</p>