

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 770)

-----  
Set ¼ sec. post, from which  
A Fir 4" dia., bears S.75°W., 2 lks. dist.  
A Fir 5" dia., bears N.5°W., 35 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 49/68

-----  
Looked for, not found.

Survey by R.E. Stuntzner - For: Reservation Ranch - Oct. 8, 1974 - C.S. File 58/10

-----  
Found no evidence of original 1/4 corner.  
Set 1/2" Iron pipe at proportionate distance, from which  
SW. Corner of a cabin bears N.23°E., 5.8 ft.  
10" Maple bears N.77°W., 14.1 ft.  
20" Fir bears N.78°E., 35.2 ft.

Fd. 1/2" IP & 2 BTs 5/2018 by A DeGroot - M171-41