

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by William A. Eimstad - For: J.H. Baxter Company -
Oct. 1981 - M 89-25

Set 5/8" x 30" Rebar at corner., from which
19" True Fir bears N.40°W., 13.7 ft. scribed C¼ S21 BT.
13" True Fir bears S.60°W., 6.0 ft. scribed C¼ S21 BT.

Adam DeGroot - For: Bruce & Ann Cole - May 2018 - M171-41

Found - A 5/8" iron rod by Eimstad in 1981 per M89-25, firmly
set flush with the ground

From which the remains of the 1981 BTs -

A 19" rotted fir stump bears N.67°45'W. 9.7 ft w/no mks
visible (N.40°W. 13.7 ft) {N.40°45'W. 13.6 ft}

A 13" rotted fir stump bears S.43°W. 8.1 ft w/no mks
visible (S.60°W., 6.0 ft) {S.47°30'W., 6.0 ft}

Note - The above found stumps are exceedingly rotted. I
searched at the 1981 and 1988 record locations
and did not find any evidence. These are the only
stumps in the corner location which somewhat
match the previous records.

New BTs- A 7" Fir bears N.70°45'E., 9.5 ft. scribed "C¼S21
BT" on dbl blaze

A 7" Fir bears S.23°30'E., 17.6 ft scribed "C¼S21
BT" on dbl blaze

New RMs- A 5/8"x30" iron rod w/YPC "BTS ENG-SURV" bears
S.70°51'44"W., 18.50 FT

A 5/8"x30" iron rod w/YPC "BTS ENG-SURV" bears
N.24°44'09"W., 25.83 ft.