

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 771)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.5°W., 37 lks. dist.
A Hemlock 12" dia., bears S.6°W., 56 lks. dist.

A.R. Evans - Wit: R. Matthews; C. Blosser; F. Wolfer - Nov. 3, 1949 - Vol. 5 Pg. 30

Found O.B.T. for ¼ cor. 30" Fir, now 42", N.5°W., 37 lks. Blaze very plain, scribe mark visible.
Set 2" x 60" Iron pipe for ¼ cor., from which
20" Cedar bears N.65°E., 32.0 ft., blazed and scribed "¼ S16 CS BT".
42" D.Fir bears S.53°E., 50.5 ft. blazed and scribed "¼ S21 CS BT".

Fd. OK, July 1953 by C. Bayles - C.S. File 41/183

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Nov. 1964 - C.S. file 49/68-43

Found - 2" I.Pipe set by Evans.
36" Cedar N.65°E., 32.0 ft., opened and found good scribing.
42" Fir stump S.53°E., 50.5 ft. bark scribed "¼ S CS BT".
New BT - 8" Hemlock S.68°E., 8.0 ft. mkd. "¼ S21 CS BT"
Did Not Set Brass Cap.

Fd. OK, Oct. 1981 by W. Eimstad - M 89-25
FD. Ok by Kris DeGroot 10/2006 - M146-46A