

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 772)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.50°W., 2 lks. dist.  
A Fir 12" dia., bears S.36°W., 6 lks. dist.

Douglas County Surveyors Office - James Byron, - Jan. 1969  
C.S. File 54/14-46A

-----  
Looked for, not found.  
Find old blazed E-W line. No O.B.T.s or stumps old enough for original.

David Edwards, surveyed for Seneca Jones Timber Co.,  
Oct. 1998 M130-42

-----  
Set - 5/8" x 30" steel pin w/red plastic cap mkd. "D.A. EDWARDS-LS2339" by single proportionate measure.  
New Accessories -  
6" dia. Fir, bears N.71°E., 11.11 ft.  
31" dia. Fir, bears S.55°E., 16.45 ft.  
7" dia. Fir, bears S.46°W., 36.45 ft.  
8" dia. Fir, bears N.43°W., 38.98 ft.  
Trees were scribed according to the 1971 B.L.M manual, and measured to center of tree at root crown.