

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34; and 3 & 4, T22-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 752)

Set post cor. of secs. 3, 4, 33 and 34, from which
A Fir 30" dia., bears N.22°E., 47 lks. dist.
A Fir 7" dia., bears N.19°W., 41 lks. dist.
A Fir 10" dia., bears S.77°W., 53 lks. dist.
A Fir 3" dia., bears S.37°E., 54 lks. dist.

Fd. and used in GLO survey by Wm. P. Wright, under Contract #514, dated August 27, 1884. (DCSO records, Vol. 4 Page 1363)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Nov. 1964 - C.S. File 49/68-32

Found old Cedar stake. According to Mr. Brown, property owner, he first saw this stake in same position, in 1913, and it was not a new stake at that time. No BTs found but old Fir stump to NE. fits call for NE. BT. No renewal recorded. Haines' tag.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16954-55)

Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 24" in the ground, with brass cap mkd:

T 21 S R 4 W
S 33 | S 34
S 4 | S 3
T 22 S R 4 W
1980

from which

A Cedar 6" dia., bears N.56°E., 30 lks. dist. mkd. T21S R4W S34 BT.

A Cedar 6" dia., bears S.53 3/4°E., 27 lks. dist. mkd. T22S R4W S3 BT.

A Fir 12" dia., bears S.55½°W., 45 lks. dist. mkd. T22S R4W S4 BT.

A Fir 6" dia., bears N.33½°W., 59 lks. dist. mkd. T21S R4W S33 BT.

FD OK by D. Peel 7/88, M 106-48

(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34; and 3 & 4, T22-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Daniel Baker, For: Weyerhaeuser - Jan. 1995 - M119-54

Found - U.S.B.L.M Brass cap dated 1980.
13" Cedar, N.56°E., 19.7 ft. - closed face (Rec. N.56°E., 30 lks. (1980 BLM)
9" Cedar, S.53½°E., 18.0 ft. - closed face (rec. S.53 3/4°E., 27 lks. (1980 BLM)
15" Fir, S.56°W., 29.5 ft. - closed face (rec. S.55½°W., 45 lks. (1980 BLM)
8" Fir, N.33 3/4°W., 38.7 ft. - down and out. (rec. N.33½°W., 59 lks. (1980 BLM)
New BT - 7" Fir, N.52°W., 8.5 ft. to "W" nail scribed "T21S R4W S33 BT"

Fd. OK, Jan. 4, 1996 - D. Baker - M 124-4