

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 762-63)

Set ¼ sec. post, from which
A Fir 8" dia., bears N.85°W., 25 lks. dist.
A Redwood 8" dia., bears N.37°E., 16 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Nov. 6, 1964 - C.S. File 49/68

Found - Old Cedar stake scribed "¼".
Found Cedar stump S.72°E., approx. 60 ft. dist.,
found scribing "¼S". Ring count shows approx. age
60 years. BT scar plainly visible but not
opened.
No trace found of original BTs.
No renewal recorded. Stake is probably 60 yrs. old. Haines'
BT tag.

Douglas Co. Surveyors Office - L.E. Monrean; P.L. Earle; M. Tompkins - Aug. 31, 1976 - C.S. File 59/18-28

Not found
Found old cedar stake, no markings.
Found Cedar stump S.72°E., 51.9 ft. scribed ¼ S.
Found Haines tag on small cedar.
No original evidence found, Did not set monument.

Survey by Donald Peel - For: Weyerhaeuser Co. - July 13, 1988
- M 106-48

Set 2" x 42" Iron pipe with brass cap mkd. "T21S R4W 1/4 S331S34 PLS 752 1988", from which new BTs:
10" Fir N.57°E., 7.8 ft. scribed "¼ S33 BT"
14" Fir N.0½°W., 15.5 ft. scribed "¼ S33 BT".
30" Cedar stump, unknown origin, opened to visible
scribing, bears S.22°13'18"E. (approx. 70 years of
overgrowth)

Fd. OK, Jan. 4, 1996 by D. Baker - M 124-4

David Wellman - For: Summerwood Inc. - June 1999 - M 132-12

Found - 2½" brass cap, 1988 per M106-48, 0.4 ft. above ground
10" Fir stump, N.57°E., 7.8 ft. to "W" nail - scribe
visible - rec: N.57°E., 7.8 to "W" nail. 1988
continued next page

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	16" Fir N.0½°W., 16.0 ft. to nail fd. side center - closed face - rec: N.0½°W., 16.0 ft. to "W" nail 1988
	30" rotten Cedar stump, S.22¼°E., 26.1 ft. to center - visible scribe - rec: unknown
Set -	18" Cedar, S.81½°W., 26.3 ft. to spike set side center, scribed: "¼ S33 BT"
	15" Fir stump, S.47°E., 24.4 ft. to spike set side center scribed "BT"