

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 764)

Set post cor. of secs. 21, 22, 27 and 28, from which
A Fir 8" dia., bears S.46°E., 43 lks. dist.
A Fir 10" dia., bears N.68°W., 9 lks. dist.
A Maple 12" dia., bears S.29°W., 52 lks. dist.
A Maple 12" dia., bears N.70°W., 52 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 26, 1958 - C.S. File 49/68-3

Found - Orig. 10" now 34" R.Fir N.68°E., (rec. N.68°W., 5.9 ft.) I open this BT, find good scribing (scribed high 4.5 ft. above ground("T21S", checks for ring count. This BT has been rescribed by Thiel (bark scribed) "22 BT".
Clump of Maples that checks bearing and distance for orig. SW. BT.
No trace of other BTs found.
Also find large flat stone with +. Cross at old fence post. Stone bears S.11°W., 3.4 ft. from section corner.

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 4 W
S 21 | S 22
S 28 | S 27
1958

New BTs- 4" R.Fir bears N.71p°W., 18.0 ft. scribed S21 CS BT.
17" W.Fir bears N.50°E., 8.6 ft. scribed S22 T21S R4W CS BT.
10" Maple bears S.28½°W., 36.2 ft. scribed S28 T21S R4W CS BT.
19" W.Fir bears S.60°E., 38.8 ft. scribed S27 T21S R4W CS BT.

Fd. OK, by DCSO, Oct. 1964 - C.S. File 49/68-39

Cor. Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1026, surveyed July 1980/March 1981 - (DCSO records Vol. 44 Page(s) 16963)

(Fd. 1958 DCSO brass cap, 3 orig. BTs.; 4 BTs by Byron and the basalt stone (that was not of record)

(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, Oct. 1981 by Eimstad - M 89-25
Fd. OK, Jan. 1993 by R. Dolan - M 116-41

BLM dependent resurvey by Harvey M. Christensen, LS 2603, under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCS0 records Vol. 55 Page(s) 21534-5)

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree
A decayed fir snag, 34" dia., bears N.68°E., 5.9 ft., with faint illegible scribe marks visible on open blaze. (Record, 58" dia.)

and the remains of BTs mkd by Byron reported by Jelly & Rogers
A fir snag, 25" dia., bears N.50°E., 8.6 ft., with a healed blaze. (Record, 8.9 ft.)

A fir, 28" dia., bears S.60°E., 38.9 ft., with a healed blaze.

A root hole, bears N.71½°W., 18.5 ft., with a fir, 14" dia., laying alongside, with a healed blaze.

and new bearing trees

A D.Fir, 7" dia., bears S.73°W., 16.7 ft., mkd. T21S R4W S28 BT.

A D.Fir, 22" dia., bears N.16°W., 46.5 ft., mkd. T21S R4W S21 BT.

No suitable bearing tree available within limits in sec. 22. From the cor., a point established as the cor. of secs. 21, 22, 27, and 28, by person(s) unknown, reported as the cor. by the Oregon State Highway Department, in 1952, Drawing No. IR-5-276, Records of the Department of Transportation, and reported as a bearing object by Jelley and Rogers, bears S.13°00'00"W., 3.3 ft., monumented with a basalt stone, 3x3 ft., projecting 3 " above ground, marked X on top. This point is not utilized in this survey.

Also from the cor., North, 10.0 ft. dist., a wire fence, bears East and West.

Set 5 foot steel fence post alongside cor.