

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 766-7)

Set ¼ sec. post, from which
A Fir 36" dia., bears N.58°E., 68 lks. dist.
A Fir 10" dia., bears S.32°W., 57 lks. dist.

Douglas County Surveyors Office - James W. Byron, Surveyor
C.S. File 54/14-22A - April 3, 1969

Corner searched for, not found.
Fd. blazed line not too old. Tree mkd. with "X" and numerous blazes, very old logging.

Survey by Gary T. Johnston - For: June 16, 1986 - M 102-14

Corner set by proportion, original not found.
Set 5/8" x 30" iron rod, 26" in ground with 1¼" plastic cap stamped "Willamette Industries, Inc." from which
6" D. Fir bears N.84°W., 10.5 ft. to the face, mkd. ¼ S9 BT
12" D. Fir bears S.66°E., 15.9 ft. to face, mkd. ¼ S10 BT.
Painted faces orange. Placed Willamette Ind. yellow bearing tree tags on both trees. Set white fiberglass post 1.0 ft. South of corner.