

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 767)

Set post cor. of secs. 3, 4, 9 and 10, from which
A Cedar 8" dia., bears N.68°W., 3 lks. dist.
A Cedar 12" dia., bears N.54°E., 16 lks. dist.
A Fir 3" dia., bears S.65°E., 26 lks. dist.
A Fir 10" dia., bears S.12°W., 37 lks. dist.

J.W. Cole, Deputy - Wit: P.D. Wolford; Frank Warren - Sept. 30, 1920 - Field Book 48 Pgs 55 & 56 (and "old" cor. book, Pg. 9)

Renewed cor. from remains of three original BTs.
Set a 3" x 3" x 36" Ewe wood post, from which
A W.Fir 30" bears N.39½°W., 11.6 ft.
A W.Fir 24" bears N.54°E., 59.2 ft.
A Red Fir 18" bears S.20°E., 46.5 ft.
A Chinquapin 10" bears S.29½°W., 59.5 ft.
Marked all trees "CS BT".

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April 1969 - C.S. File 54/14-22

Found - Old charred yew wood post.
Orig. 8" now 24" Cedar burned stump, N.68°W., 2.0 ft. "BT" scribe visible on open blaze.
Orig. 10" now 48" Fir snag, injured and hollow S.12°W., 24.4 ft., no scribe found.
No trace other original BTs.
Cole's 18" now 24" Fir, sawed stump S.20°E., 46.5 ft. too low for scribe.
No trace of Cole's other BTs.

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 4 W
S 4 | S 3
S 9 | S 10
1969

New BTs- 8" D.Fir N.84°E., 37.2 ft. mkd. T21S R4W S3 CS BT.
8" Chinquapin S.60°W., 22.0 ft. T21S R4W S9 CS BT.
8" Chinquapin N.54°W., 30.4 ft. T21S R4W S4 CS BT.
No suitable tree in section 10.

Fd. OK, June 16, 1986 by Johnson - M 102-14
Fd. OK, April 1990 by D. Peel - M 110-2

(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Resurvey by Daniel N. Patterson and Craig L. Wanless, Cadastral Surveyors, under Group #1705, surveyed Aug/Oct. 1993 - (DCSO records Vol. 51 Page(s) 19247-48)

 The Sec. Cor., perpetuated by Cole in 1920, further perpetuated by Tracy in 1969, further perpetuated by Johnston in 1986, further perpetuated by Peel in 1990, monumented with an iron pipe 1" dia., firmly set, projecting 14" above ground, with brass cap mkd. in 1969, from which the remains of original bearing trees:

A decayed Fir stump 48" dia., bears S.7½°W., 38½ lks. dist., no marks visible. (Rec. S.12°W., 37 lks.)

A decayed Cedar stump, size indeterminate, bears N.68°W., 3 lks. dist., no marks visible.

and bearing trees mkd. by Tracy:

A Fir 21" dia., bears N.84°E., 56½ lks. dist., with healed blaze.

A Chinquapin 12" dia., bears S.60°W., 33 lks. dist., with fragmentary scribe marks visible on partially open blaze.

and a new bearing tree:

A Fir 15" dia., bears S.21°E., 25½ lks. dist., mkd. T21S R4W S10 BT.

No suitable trees available in sec. 4.