

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Sec. 34; and 3 of T22-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 751)

Set ¼ sec. post, from which
A Laurel 10" dia., bears S.38°W., 10 lks. dist.
A Laurel 8" dia., bears N.65°E., 9 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Nov. 6, 1964 - C.S. file 49/68-32

Found stake mkd. "Approx. ¼ Cor." only.

Douglas Co. Surveyors office - James Byron - (probably 1968 or 1969) - C.S. File 54/14

Find steel fence post mkd. "approx ¼". No original BTs found or no new BTs. Extensive numbers of stumps and snags chopped and sawed open in apparent previous searches.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16954)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 21 S R 4 W
1/4 $\frac{S\ 34}{S\ 3}$
T 22 S R 4 W
1980

from which
A Grand Fir 16" dia., bears North, 47½ lks. dist. mkd. ¼ S34 BT.
A Grand Fir 16" dia., bears S.18½°W., 70 lks. dist. mkd. ¼ S3 BT.

FD OK by D. Peel, 7/88 - M 106-48

Survey by Daniel Baker - For: Weyerhaeuser Co. - Jan. 1995 - M 119-54

Condition Report Only
Found - US BLM brass cap dated 1980.
17" W.Fir N.2½°E., 47.5 ft. to spike, visible scribe. (Rec. North 47.5 lks.) 1980 BT.
(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for sec. 34; & 3, T22-4

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

20" W.Fir S.14½°E., 44.8 ft. to spike, closed face.
(Rec. S.18½°W., 70 lks.) 1980 BT.
Spikes were set this survey at side center.

Fd. OK, Jan. 4, 1996 by D. Baker - M 124-4