

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 440240

PRIMARY CORNER DESCRIPTION C ¼ Sec. 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Harvey M. Christensen, LS 2603, under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCSO records Vol. 55 Page(s) 21535-6)

-----  
Point for the center ¼ sec. cor. of sec. 27, at intersection of the N and S center line with the E and W center line. Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T 21 S R 4 W  
C 1/4 S 27  
2008

from which  
A D.Fir, 18" dia., bears N.53°E., 13.2 ft., mkd. C¼ S27 BT  
A D.Fir, 12" dia., bears S.15°E., 24.3 ft., mkd. C¼ S27 BT  
Deposit a magnet in a white plastic case at the base of the stainless steel post.  
Set two 5 ft. aluminum fence posts alongside cor.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description