

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 765)

Set ¼ sec. post, from which
A Cedar 10" dia., bears S.53°E., 47 lks. dist.
A Cedar 18" dia., bears N.47°E., 43 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Aug. 1, 1958 (Filed, April 24, 1959) - C.S. File 49/68-6

Found - Orig. 18" now 36" partly rotted Cedar stump. I open and find good scribing "BT", N.47°E., 28.4 ft.
18" Cedar stump, now partly rotted that has possible scribe marks that face to SW. from corner stump, bears S.25°E., 29.0 ft. (Rec. S.53°E., 31.0 ft.)
The compass needle indicates magnetic attraction in this area. To known East, I read S.55°E.
Set Brass cap at WIT. cor. mkd:

County Surveyors Office
T 21 S R 4 W
¼ $\frac{S\ 15}{S\ 22}$
1958

Witness corner 7 ft. East.

Fd. OK, Oct. 1981 by W. Eimstad - M 89-25
Fd. OK by R. Bath, May 1997 - CS6532-5 A&B