

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 767)

Set ¼ sec. post, from which
A Laurel 12" dia., bears S.76°E., 7 lks. dist.
A Laurel 12" dia., bears N.15°W., 28 lks. dist.

BLM resurvey by Daniel N. Patterson and Craig L. Wanless, Cadastral Surveyor, under Group #1705, surveyed Aug/Oct. 1993 - (DCSO records Vol. 51 Page(s) 19246-47)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 4 W
¼ $\frac{S 3}{S 10}$
1993

from which

A Cedar 14" dia., bears S.45°W., 35 lks. dist. mkd. ¼ S10 BT.

A Fir 9" dia., bears N.11°W., 2½ lks. dist. mkd. ¼ S3 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.