

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 751)

Set post cor. of secs. 2, 3, 34 and 35, from which
A Fir 30" dia., bears S.50°W., 34 lks. dist.
A Fir 20" dia., bears S.10°E., 82 lks. dist.
A Fir 6" dia., bears N.48°W., 42 lks. dist.
A Laurel 18" dia., bears N.48°W., 42 lks. dist.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under special instructions dated August 15, 1901 (DCSO records Vol. 4 Page(s) 1376-77)

The Sec. cor., which is a sandstone, 12x8 ins., 6" above ground, marked with 2 notches on E. and 4 notches on W. edges, from which
A Fir 20" dia., bears S.87°E., 68 lks. dist. mkd. T22S R4W S2 BT.
The original BT had fallen, the others are as marked and described by the surveyor general.
I destroy all marks referring to secs. 2 and 3.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam and Vernon "Ray" Tracy, crew - March 1962 - C.S. File 49/42-55

Found - Laurel tree, now 24", N.48°W., 27.7 ft. Faint scribing visible on old rotted face "S3 T2 R".
Old Fir stump 42", S.50°W., 22.4 ft. Bark facing corner shows old smoothed off face.
Old Fir stump 32", S.87°E., 44.9 ft. (slope dist) No scars or scribing found. (Thiel's tree)
Mound of rocks at corner.
Set Brass cap at cor. mkd: County Surveyors Office
T21S R4W S34|S35
1962
New BTs -20" I.Cedar N.64°E., 28.0 ft. mkd. T21S R4W S35 CSBT
7" W.Fir N.19°W., 15.6 ft. mkd. T21S R4W S34 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16952-53)

The Sec. cor., perpetuated and recorded by Godfrey in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground with properly mkd. brass cap
(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees:
A Fir 22" dia., bears N.77½°E., 43 lks. dist., with healed blaze. (Rec. N.83°E.)
A sawed Fir stump 42" dia., bears S.55°W., 34 lks. dist. no marks remaining. (Rec. S.50°W.)
A Madrone 25" dia., bears N.48°W., 42 lks. dist. with fragmentary scribe marks visible on open blaze.
a bearing tree mkd. the Thiel
A sawed Fir stump 32" dia., bears S.87°E., 68 lks. dist., no marks visible.
and bearing tree mkd. by Godfrey:
A Cedar 23" dia., bears N.62°E., 42 lks. dist., with fragmentary scribe marks visible on open blaze.
A Fir 13" dia., bears N.22°W., 23½ lks. dist. with healed blaze.

BLM dependent resurvey by Harvey M. Christensen, LS 2603, under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCS0 records Vol. 55 Page(s) 21527-8)

The cor. of secs. 34 and 35 only, on the S bdy. of T21S R4W reported by Jelly and Rogers, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd.
from which the remains of orig BTs reported by Jelly & Rogers
A decayed fir stump, 42" dia., bears S.55°W., 22.4 ft. no marks visible.
A decayed madrone stub size indeterminate, bears N.48°W. 27.7 ft., no marks visible.
and the remains of a bearing tree mkd. by Thiel
A decayed fir stump, 32" dia., bears S.87°E., 40.7 ft., no marks visible. (Record, and slope dist. 44.9 ft.)
and the remains of bearing trees mkd. by Godfrey, in 1962
A cedar, 28" dia., bears N.62°E., 27.7 ft. with a healed blaze.
A fir, 18" dia., bears N.22°W., 15.5 ft., with a healed blaze.
Set 5 ft. aluminum fence post alongside cor.