

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 758)

-----  
Set ¼ sec. post, from which  
A Fir 40" dia., bears S.80°E., 31 lks. dist.  
A Fir 10" dia., bears S.55°W., 45 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy -  
Nov. 20, 1964 - C.S. File 49/68-44

-----  
Looked for, not found.

Survey by Donald Peel - For: Weyerhaeuser Co. - May 20, 1987  
M 104-28

-----  
Set 2" x 42" Iron pipe with brass cap stamped "T21S R4W 1/4  
S27|S26 PLS 752 1987". from which  
A 12" Fir bears S.60°E., 7.9 ft. scribed "¼ S26 BT"  
A 20" Fir bears S.31°W., 19.3 ft. scribed "¼ S27 BT"

Found OK by D. Edwards, July 2002 - M140-43

BLM dependent resurvey by Harvey M. Christensen, LS 2603,  
under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCSO  
records Vol. 55 Page(s) 21529-30)

-----  
The ¼ sec cor of secs. 26 & 27 reestablished by proportionate  
measurement by Peel, in 1987, there is no remaining evidence  
of the original cor. therefore, this position is accepted as  
the corner, monumented with an iron post, 2" dia., firmly set,  
projecting 6" above the ground, with brass cap (properly) mkd.  
from which the remains of the bearing trees mkd. by Peel  
A sawed fir stump, 14" dia., 6 ft. high, bears S.60°E.,  
7.9 ft., with a healed blaze.  
A fir, 27" dia., bears S.31°W., 19.5 ft., with a healed  
blaze.  
and a new bearing tree  
A D.Fir, 19" dia. bears N.43¾°W., 25.5 ft. mkd. ¼ S27 BT  
Set 5 ft. aluminum fence post alongside cor.