

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 759)

-----  
Set ¼ sec. post, from which  
A Fir 70" dia., bears N.54°E., 21 lks. dist.  
A W.Oak 8" dia., bears N.45°W., 68 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1026, surveyed July 1980/March 1981 - (DCSO records Vol. 44 Page(s) 16959)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 21 S R 4 W  
1/4  
S 22 S 23  
1980

from which  
A Fir 10" dia., bears N.89½°E., 36 lks. dist. mkd. ¼ S23 BT.  
A Fir 13" dia., bears S.24½°W., 28 lks. dist. mkd. ¼ S22 BT.