

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 761)

-----  
Set ¼ sec. post, from which  
A Cedar 24" dia., bears N.80°W., 44 lks. dist.  
A Maple 10" dia., bears N.50°E., 27 lks. dist.

Oscar Thiel - March 1899 - Vol. 2 Page 261

-----  
Set a Cedar post, from which  
A Fir 40" dia., bears S.45°W., 61 lks. dist.  
The NE. original BT still standing but marks obliterated.  
I remark the same.  
The other BT had fallen down.  
Present were Alex Wright and J.A. Tramel.

Douglas Co. Surveyors Office - Gary Langlitz; A. Vic Cangie; M.L. Tompkins, crew - Oct. 27, 1976 - C.S. File 59/24-47

-----  
Found - A wooden post set by Herm Pieske for Sun Studs. It was set at the intersection point of an E-W and N-S fence line.  
36" Cedar, down and rotted. No trace of scribing or blaze.  
21" Maple, alive but rotted through the face and middle of the tree. No trace of scribing.  
No trace of original corner post.  
WE DO NOT SET THE CORNER FOR LACK OF EVIDENCE.

Survey by Les Roberts - For: Willamette Industries, Inc. - April 1996 - M 123-56

-----  
Found - 44" Fir stump S.45°W., 40.3 ft., scar visible, no scribing found.  
Corner falls on old N-S fence line.  
A 4" x 4" square Cedar post, bears N.15°E., 8.5 ft.  
Set 5/8" x 30" Iron pin with yellow plastic cap stamped "ROBERTS P.L.S. 1039", from which  
4" W.Fir N.42°E., 29.7 ft., scribed/painted red.  
12" Fir S.4°W., 15.0 ft., scribed/painted red.  
12" Maple S.84°E., 45.5 ft., scribed/painted red.  
14" Maple N.23°W., 22.0 ft., scribed/painted red.

Found OK by K. Hoffine, June 2000 - M135-35 A&B  
Fd. ok by Wm. Eimstad, 4/2004 - M145-67