

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 761)

-----  
Set post corner of secs. 2, 3, 10 and 11, from which  
A Fir 70" dia., bears N.30°W., 9 lks. dist.  
A Fir 6" dia., bears N.48°E., 36 lks. dist.  
A Fir 10" dia., bears S.70°E., 43 lks. dist.  
A Laurel 8" dia., bears S.12°W., 20 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Jan. 1969 - C.S. File 54/14-46

-----  
Found - Very old 4x4x8" Cedar post at corner, no marks.  
Orig. 70" Fir now 72" sawed stump N.30°W., 5.9 ft.,  
no scribe.  
Orig. 10" now 32" Fir, turned out, S.70°E., 28.4  
ft., open and find scribe.  
Hole where orig. NE. BT, would have been.  
No trace of SW. original BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 21 S R 4 W  
S 3 | S 2  
S 10 | S 11  
1969

New BTs- 10" R.Fir S.22°W., 19.3 ft. mkd. T21S R4W S10 CSBT  
7" D.Fir S.30½°E., 17.0 ft. mkd. T21S R4W S11 CSBT  
5" D.Fir N.83°W., 11.5 ft. mkd. S3 CS BT.  
18" I.Cedar, N.55°E., 54.9 ft. mkd. T21S R4W S2 CSBT

Fd. OK, Oct. 1990 - M 110-72

Fd. and used in BLM resurvey by Daniel N. Patterson and Craig L. Wanless, Cadastral Surveyors, under Group #1705, surveyed Aug/Oct. 1993 - (DCSO records Vol. 51 Page(s) 19246)

Fd. OK, Oct. 1994 - M 120-70

Fd. OK, April 1996 by L. Roberts - M 123-56