

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 2 and 3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 762)

-----  
Set ¼ sec. post, from which  
A Fir 20" dia., bears S.55°W., 27 lks. dist.  
A Fir 10" dia., bears N.80°E., 21 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Dec. 12, 1967 - C.S. File 54/14-26

-----  
We find old squared post and stumps as follows:  
32" Fir stump S.55°W., 18.0 ft. No scribe found on stump or log laying nearby.  
Shattered Fir snag N.82°E., 14.0 ft. No scribe found.  
This was a double Fir  
Blazed for N-S line. We find nothing to substantiate this cor. We find no axe work except recent.

Survey by Charles Guile - For: Weyerhaeuser Co. - Feb. 27, 1987 - M 103-68 and C.S. File 63/45

-----  
Set 1" x 36" Iron pipe with cap from which  
Rotted stump hole bears N.79°E., 14.4 ft. with scribe.  
20" chinquapin bears N.67°W., 6.4 ft. to nail.  
17" Fir bears S.72°E., 23.9 ft. to nail.  
New BTs-  
14" Fir bears N.2°W., 14.7 ft. to "W" nail scribed "E¼ S3 BT"  
11" Fir bears S.20°E., 28.4 ft. to "W" nail scribed "W¼ S2 BT"  
Also found a steel fence post bearing N.19°E., 0.35 ft.

BLM resurvey by Daniel N. Patterson and Craig L. Wanless, Cadastral Surveyors, under Group #1705, surveyed Aug/Oct. 1993 - (DCSO records Vol. 51 Page(s) 19251-52)

-----  
The ¼ sec. cor., perpetuated by VanDomelin, BLM project Engineer in 1968, recorded in the Eugene District, BLM, Eugene, Oregon, subsequently perpetuated by Guile in 1987, monumented with an iron pipe, 1" dia., firmly set, projecting 4" above the ground with plastic cap mkd. GUILLE PLS 472, from which the remains of the original bearing trees;  
A root hole bears N.80°E., 21 lks. dist.  
A sawed Fir stump 24" dia., bears S.55°W., 28 lks. dist., no marks visible on open blaze. (Rec. 27 lks.)  
and the remains of bearing trees mkd. by VanDomelin:  
(Cont. Next Page)

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 17" dia., bears S.72½°E., 37½ lks. dist. with nail at base of snag.  
A Chinquapin 21" dia., bears N.67°W., 10½ lks. dist., with nail at base of tree.  
and bearing trees mkd. by Guile:  
A Fir 13" dia., bears S.20°E., 44 lks. dist., with healed blaze.  
A Fir 17" dia., bears N.1½°W., 24 lks. dist., with healed blaze.  
At the corner point  
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 21 S R 4 W  
    ¼  
    S 3 S 2  
    1993  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.  
The corner is located at SW. corner of logged area, edges extend N. and E.

Fd. OK, Oct. 1994 by C. Guile - M 120-70