

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 758)

Set ¼ sec. post, from which
A Fir 24" dia., bears S.64°W., 9 lks. dist.
A Fir 18" dia., bears N.10°W., 6 lks. dist.

Survey by Gilbert Gardner - For: W.A. Woodard Lumber Co. - July/Dec. 1955 - C.S. File 42/131 and M 2-16

Set a 2" Iron pipe half way between section corners.
Marked 2 new Bts:
14" I.Cedar N.50½°E., 35.0 ft.
24" I.Cedar S.80°W., 110.6 ft.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #398 Surveyed, April/May 1958 - (DCSO records Vol. 31 Page(s) 12991)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 21 S R 4 W
¼ $\frac{S 26}{S 35}$
1958

from which
A Fir 10" dia., bears N.1½°E., 61 lks. mkd. ¼ S26 BT
A Fir 17" dia., bears S.57¼°E., 379 lks. mkd. ¼ S35 BT.
From this point, a locally established cor., bears N.17°07'E., 35 lks. dist., monumented with an iron pipe, 1¼" dia., protruding 4 ft. above ground, firmly set, from which
A Cedar 15" dia., bears N.52°E., 53½ lks. mkd. ¼ S 276 BT
A Cedar 27" dia., bears S.81°W., 166½ lks. mkd. ¼ S 276 BT

Fd. OK, May 1987 by D. Peel - M 104-28

BLM dependent resurvey by Harvey M. Christensen, LS 2603, under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCSO records Vol. 55 Page(s) 21524-5)

The ¼ sec. cor. of secs. 26 and 35, determined at record bearing and distance from the remains of the original BTs
A decayed fir stump, 30" dia., bears S.64°W., 5.9 ft., with illegible scribe marks visible on partially open blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir, 35" dia., bears N.10°W., 4.0 ft., with scribe marks BT visible on partially open blaze and reverse scribe marks on piece of wood laying alongside.

At the corner point

Set a stainless steel post, 30 ins. long, 2½" dia., 20 ins. in the ground, with brass cap mkd.

T 21 S R 4 W

¼ S 26
S 35

2008

from which new bearing trees

A D.Fir, 27" dia., bears S.14°W., 17.7 ft., mkd. ¼ S35 BT.

A D.Fir, 14" dia., bears S.65°E., 16.2 ft., mkd. ¼ S35 BT.

No suitable bearing tree available within limits in sec. 26. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Set 5 ft. aluminum fence post alongside cor.

From the corner, a point erroneously reestablished as the ¼ sec. cor. of secs. 26 and 35, by Roseberry, in 1958, bears N.56°20'00"W., 32.34 ft., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. as described in the official record.

Add the marks AM 2008 to the brass cap, and reset iron post 32" in the ground, with top 2" below surface. From which the bearing trees mkd. by Roseberry (due to blaze overgrowth, scribe marks were not removed)

A fir, 20" dia., bears N.1½°E., 40.3 ft., with a healed blaze.

A fir, 24" dia., bears S.57¼°E., 250.1 ft., with a healed blaze.

Also from the corner, a point reestablished as the ¼ sec. cor of secs 26 & 35, by Gardner, in 1956, bears N.26°47'30"W. 44.40 ft., monumented with an iron pipe, 1¼" dia., loosely set, projecting 48" above ground, bent and leaning W., from which bearing trees mkd. by Gardner, reported by Roseberry

A cedar, 22" dia., bears N.52°E., 35.3 ft., with a healed blaze.

A cedar, 33" dia., bears S.81°W., 109.9 ft., with a healed blaze.

This point is not properly positioned and is not utilized in this survey.